### **SAFETY DATA SHEET**



#### Alphasyn T 220

### **Section 1. Identification**

Product name Alphasyn T 220
Product code 451121-FR01
SDS no. 451121

Use of the substance/mixture Gear lubricant.

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Product type Liquid.

Supplier Castrol New Zealand Limited

73 Remuera Road Newmarket

Auckland, New Zealand

www.castrol.com/nz

Technical Helpline 0800 10 40 60

Emergency telephone number 0800 243643 (0800 CHEMHELP) (NZ use only)

**New Zealand National Poisons** 

Centre

0800 764 766 National Poison Centre

#### Section 2. Hazards identification

**HSNO Classification** REPRODUCTIVE TOXICITY - Category 2

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Routes of entry Dermal contact. Eye contact. Inhalation.

**GHS label elements** 

Signal word Warning

**Hazard statements** Suspected of damaging fertility or the unborn child.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid release to the environment.

**Response** IF exposed or concerned: Get medical attention.

Storage Store locked up.

Disposal Dispose of contents and container in accordance with all local, regional, national

and international regulations.

**Symbol** 

Other hazards which do not result in classification

None known.

Product name Alphasyn T 220 Product code 451121-FR01 Page: 1/8

Version 3.02 Date of issue 14 September 2023 Format New Zealand Language ENGLISH

## Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Synthetic base stock. Proprietary performance additives.

Ingredient name	% (w/w)	CAS number
Phenol, isobutylenated, phosphate (3:1)	≤3	68937-40-6
N-1-naphthylaniline	<1	90-30-2
9-Octadecenoic acid (Z)-, reaction products with 3-(dodecenyl)dihydro-2,5-furandione and triethylenetetramine	≤0.3	68478-81-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

**Description of necessary first aid measures** 

**Inhalation** If inhaled, remove to fresh air. Get medical attention.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery

position and get medical attention immediately. Get medical attention.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention.

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing.

Check for and remove any contact lenses. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician**Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with

extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the

product considerable distances along tissue planes.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

# Section 5. Firefighting measures

**Extinguishing media** 

from the chemical

Suitable Use foam or all-purpose dry chemical to extinguish.

**Not suitable** Do not use water jet.

Specific hazards arising Fire water contaminated with this material must be contained and prevented from

being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic

life with long lasting effects.

**Hazardous combustion** Combustion products may include the following:

phosphorus oxides

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

Hazchem code Not available.

Special precautions for fire-

fighters

products

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Product name Alphasyn T 220 Product code 451121-FR01 Page: 2/8

Version 3.02 Date of issue 14 September 2023 Format New Zealand Language ENGLISH

## Section 5. Firefighting measures

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and material for containment and cleaning up

**Small spill** 

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

### Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/ containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

# Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

No exposure limit value known.

**Biological exposure indices** 

No exposure indices known.

Product nameAlphasyn T 220 Product code 451121-FR01 Page: 3/8

Version 3.02 Date of issue 14 September 2023 Format New Zealand Language ENGLISH

## Section 8. Exposure controls/personal protection

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Hand protection Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

**Skin protection** 

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance** 

Physical state Liquid.

Colour

Odour

PH

Not available.

Not applicable.

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

**Drop Point** Not available.

Product name Alphasyn T 220 Product code 451121-FR01 Page: 4/8

Version 3.02 Date of issue 14 September 2023 Format New Zealand Language ENGLISH

# Section 9. Physical and chemical properties

Flash point

Closed cup: >210°C (>410°F) [Pensky-Martens]

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159

Vapour pressure

	Vapour Pressure at 20°C		Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Dec-1-ene, homopolymer, hydrogenated Dec- 1-ene, oligomers, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87			
triisotridecyl benzene- 1,2,4-tricarboxylate	<0	<0				
Dec-1-ene, homopolymer, hydrogenated Dec- 1-ene, oligomers, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87			
Phenol, isobutylenated, phosphate (3:1)	0.00000031	0.000000041				

Relative vapour density

**Density** <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)

Media	Result
water	Not soluble

**Viscosity** Kinematic: 220 mm<sup>2</sup>/s (220 cSt) at 40°C

Not available.

Kinematic: 25.5 mm<sup>2</sup>/s (25.5 cSt) at 100°C

**Particle characteristics** 

Median particle size Not applicable.

# Section 10. Stability and reactivity

**Chemical stability** The product is stable.

Possibility of hazardous Under normal conditions of storage and use, hazardous reactions will not occur. reactions

Under normal conditions of storage and use, hazardous polymerisation will not

occur.

**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

**Hazardous decomposition** Under normal conditions of storage and use, hazardous decomposition products

products should not be produced.

# **Section 11. Toxicological information**

Information on likely routes of exposure

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Ingestion No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

No known significant effects or critical hazards. **Eye contact** Symptoms related to the physical, chemical and toxicological characteristics

Inhalation No specific data.

Product nameAlphasyn T 220 Product code 451121-FR01 Page: 5/8

**Format New Zealand** Version 3.02 Date of issue 14 September 2023 Language ENGLISH

## **Section 11. Toxicological information**

**Ingestion** Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact** Adverse symptoms may include the following:

irritation dryness cracking

reduced foetal weight increase in foetal deaths skeletal malformations

Eye contact No specific data.

#### Potential chronic health effects

General No known significant effects or critical hazards.

**Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Eye contact

No known significant effects or critical hazards.

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

Suspected of damaging the unborn child.

Developmental effects

No known significant effects or critical hazards.

Fertility effects Suspected of damaging fertility.

## Section 12. Ecological information

#### **Ecotoxicity**

This material is harmful to aquatic life with long lasting effects.

#### Persistence and degradability

Not expected to be rapidly degradable.

#### **Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogPow	BCF	Potential
Phenol, isobutylenated, phosphate (3:1)	4.85	-	high
N-1-naphthylaniline	4.28	-	high

#### **Mobility in soil**

**Mobility** Spillages may penetrate the soil causing ground water contamination.

Soil/water partition coefficient (Koc)

Not available.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

# Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Product nameAlphasyn T 220 Product code 451121-FR01 Page: 6/8

Version 3.02 Date of issue 14 September 2023 Format New Zealand Language ENGLISH

## **Section 14. Transport information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	Not regulated.	-	-	-		-
ADG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-

PG\*: Packing group

# Section 15. Regulatory information

**New Zealand Regulatory Information** 

**HSNO Approval Number** HSR002606

**HSNO Group Standard** Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard)

Group Standard 2020

**HSNO Classification** REPRODUCTIVE TOXICITY - Category 2

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Regulation according to other foreign laws

**REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance

with the current requirements of REACH.

**United States inventory** 

(TSCA 8b)

All components are active or exempted.

**Australia inventory (AIIC)** All components are listed or exempted.

**Canada inventory status** At least one component is not listed in DSL but all such components are listed in

NDSL

**China inventory (IECSC)** All components are listed or exempted. Japan inventory (CSCL) At least one component is not listed. **Korea inventory (KECI)** At least one component is not listed. **Philippines inventory** All components are listed or exempted.

(PICCS)

**Taiwan Chemical** All components are listed or exempted.

**Substances Inventory (TCSI)** 

### Section 16. Other information

**History** 

Date of issue/Date of

revision

14 September 2023

Date of previous issue 4 September 2023.

Version 3.02

Prepared by Not available.

Key to abbreviations Varies = may contain one or more of the following 64741-88-4, 64741-89-5,

64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

**Notice to reader** 

▼ Indicates information that has changed from previously issued version.

Product nameAlphasyn T 220 Product code 451121-FR01 Page: 7/8

**Format New Zealand** Version 3.02 Date of issue 14 September 2023 Language ENGLISH

#### Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameAlphasyn T 220

Product code 451121-FR01

La company ENGLIGH

Version 3.02 Date of issue 14 September 2023

Format New Zealand Language ENGLISH

Page: 8/8