

## Cyltech 40SX

**Section 1. Identification**

<b>Product name</b>	Cyltech 40SX
<b>Product code</b>	456801-SG01
<b>SDS no.</b>	456801
<b>Use of the substance/mixture</b>	Marine engine oil For specific application advice see appropriate Technical Data Sheet or consult our company representative.
<b>Product type</b>	Liquid.
<b>Supplier</b>	Castrol Australia Pty Ltd Level 17, 717 Bourke Street Docklands, Victoria 3008 ABN 87 008 459 407 www.castrol.com.au
<b>Emergency telephone number</b>	Tel: +61 (03) 9268 4111 +61 2801 44558 (or 1800 14 14 74 within Australia)
<b>OTHER PRODUCT INFORMATION</b>	Technical Advice Helpline Number: 1300 557 998

**Section 2. Hazards identification**

<b>HSNO Classification</b>	Not classified.
This material is not classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.	
This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.	
<b>Routes of entry</b>	Dermal contact. Eye contact. Inhalation.
<b>GHS label elements</b>	
<b>Signal word</b>	No signal word.
<b>Hazard statements</b>	No known significant effects or critical hazards.
<b>Precautionary statements</b>	
<b>Prevention</b>	Not applicable.
<b>Response</b>	Not applicable.
<b>Storage</b>	Not applicable.
<b>Disposal</b>	Not applicable.
<b>Other hazards which do not result in classification</b>	Defatting to the skin. USED ENGINE OILS Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.

**Section 3. Composition/information on ingredients**

<b>Substance/mixture</b>	Mixture
Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.	

## Section 3. Composition/information on ingredients

Ingredient name	% (w/w)	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	≥10 - ≤30	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥10 - ≤30	64742-65-0
Residual oils (petroleum), solvent-dewaxed	≥10 - ≤30	64742-62-7
Residual oils (petroleum), hydrotreated	≥10 - ≤30	64742-57-0
Phenol, dodecyl-, sulfurized, calcium salts	≤10	68855-45-8
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	≤5	122384-87-6
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	≤3	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	≤3	64742-56-9
Alkylated phenol	≤0.3	74499-35-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

#### Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

#### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

### Indication of immediate medical attention and special treatment needed, if necessary

#### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

#### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

## Section 5. Firefighting measures

### Extinguishing media

#### Suitable

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

#### Not suitable

Do not use water jet.

### Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

#### Hazardous combustion products

Combustion products may include the following:  
metal oxide/oxides  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)  
sulphur oxides (SO, SO<sub>2</sub>, etc.)

#### Hazchem code

Not available.

#### Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

## Section 5. Firefighting measures

**Special protective equipment for fire-fighters** Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**For emergency responders** If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

**Precautions for safe handling** Put on appropriate personal protective equipment (see Section 8).

**Conditions for safe storage, including any incompatibilities** Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**Not suitable** Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

<b>Ingredient name</b>	<b>Exposure limits</b>
<input checked="" type="checkbox"/> Distillates (petroleum), hydrotreated heavy paraffinic	<b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b> WES-TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b> WES-TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Residual oils (petroleum), solvent-dewaxed	<b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b> WES-TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist

## Section 8. Exposure controls/personal protection

Residual oils (petroleum), hydrotreated	<p>WES-STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist</p> <p><b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b>  WES-TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist  WES-STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist</p>
Distillates (petroleum), hydrotreated heavy paraffinic	<p><b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b>  WES-TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist  WES-STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist</p>
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<p><b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b>  WES-TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist  WES-STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist</p>
Distillates (petroleum), hydrotreated light paraffinic	<p><b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b>  WES-TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist  WES-STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist</p>
Distillates (petroleum), solvent-dewaxed light paraffinic	<p><b>NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]</b>  WES-TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist  WES-STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist</p>

### Biological exposure indices

No exposure indices known.

### Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

## Section 8. Exposure controls/personal protection

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye protection

Safety glasses with side shields.

### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

### Skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

#### Physical state

Liquid.

#### Colour

Amber. [Dark]

#### Odour

Not available.

#### pH

Not applicable.

#### Melting point/freezing point

Not available.

#### Boiling point, initial boiling point, and boiling range

Not available.

#### Drop Point

Not available.

#### Flash point

☑ Closed cup: 232°C (449.6°F) [Pensky-Martens ASTM D 93]

#### Auto-ignition temperature

Not available.

#### Vapour pressure

Ingredient name	Vapour Pressure at 20 °C			Vapour pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Residual oils (petroleum), solvent-dewaxed	<0.08	<0.011	ASTM D 5191			
Residual oils (petroleum), hydrotreated	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			

## Section 9. Physical and chemical properties

**Relative vapour density** Not available.  
**Density** <1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15°C  
**Solubility(ies)**

Media	Result
water	Not soluble

**Viscosity**  Kinematic: 222.2 mm<sup>2</sup>/s (222.2 cSt) at 40°C  
Kinematic: 19 to 20 mm<sup>2</sup>/s (19 to 20 cSt) at 100°C

### Particle characteristics

**Median particle size** Not applicable.

## Section 10. Stability and reactivity

**Chemical stability** The product is stable.  
**Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous reactions will not occur.  
Under normal conditions of storage and use, hazardous polymerisation will not occur.  
**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).  
**Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.  
**Hazardous decomposition products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.  
**Ingestion** No known significant effects or critical hazards.  
**Skin contact** Defatting to the skin. May cause skin dryness and irritation.  
**Eye contact** No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** No specific data.  
**Ingestion** No specific data.  
**Skin contact** Adverse symptoms may include the following:  
irritation  
dryness  
cracking  
**Eye contact** No specific data.

### Potential chronic health effects

**General** USED ENGINE OILS  
Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.  
**Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.  
**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.  
**Skin contact** Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.  
**Eye contact** No known significant effects or critical hazards.  
**Carcinogenicity** No known significant effects or critical hazards.  
**Mutagenicity** No known significant effects or critical hazards.  
**Teratogenicity** No known significant effects or critical hazards.  
**Developmental effects** No known significant effects or critical hazards.  
**Fertility effects** No known significant effects or critical hazards.

## Section 11. Toxicological information

### Aspiration hazard

#### Name

Distillates (petroleum), hydrotreated heavy paraffinic  
Distillates (petroleum), solvent-dewaxed heavy paraffinic  
Distillates (petroleum), hydrotreated light paraffinic  
Distillates (petroleum), solvent-dewaxed light paraffinic

## Section 12. Ecological information

**Ecotoxicity** No known significant effects or critical hazards.

### Persistence and degradability

Not expected to be rapidly degradable.

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Phenol, dodecyl-, sulfurized, calcium salts	10.1	-	high
Alkylated phenol	6.1	-	high

### Mobility in soil

**Mobility** Spillages may penetrate the soil causing ground water contamination.

**Soil/water partition coefficient (K<sub>oc</sub>)** Not available.

**Other ecological information** Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	Not regulated.	-	-	-		-
ADG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-

PG\* : Packing group

## Section 15. Regulatory information

### New Zealand Regulatory Information

<b>HSNO Approval Number</b>	None assigned.
<b>HSNO Group Standard</b>	None assigned.
<b>HSNO Classification</b>	Not classified.

### Regulation according to other foreign laws

<b>REACH Status</b>	For the REACH status of this product please consult your company contact, as identified in Section 1.
<b>United States inventory (TSCA 8b)</b>	All components are active or exempted.
<b>Australia inventory (AIC)</b>	All components are listed or exempted.
<b>Canada inventory status</b>	All components are listed or exempted.
<b>China inventory (IECSC)</b>	All components are listed or exempted.
<b>Japan inventory (CSCL)</b>	All components are listed or exempted.
<b>Korea inventory (KECI)</b>	All components are listed or exempted.
<b>Philippines inventory (PICCS)</b>	All components are listed or exempted.
<b>Taiwan Chemical Substances Inventory (TCSI)</b>	All components are listed or exempted.

## Section 16. Other information

### History

<b>Date of issue/Date of revision</b>	9 April 2024
<b>Date of previous issue</b>	6 March 2024.
<b>Version</b>	22
<b>Prepared by</b>	Not available.
<b>Key to abbreviations</b>	Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

### Notice to reader

✔ **Indicates information that has changed from previously issued version.**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.