SAFETY DATA SHEET



Castrol Transmax Manual FE 75W

Section 1. Identification

Product name Castrol Transmax Manual FE 75W

Product code 469681-DE01

SDS no. 469681

Use of the substance/mixture Manual transmission fluid

For specific application advice see appropriate Technical Data Sheet or consult our

company representative. Manual transmission fluid

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Product type Liquid.

Supplier Castrol New Zealand Limited

73 Remuera Road Newmarket

Auckland, New Zealand

www.castrol.com/nz

Technical Helpline 0800 10 40 60

Emergency telephone number 0800 243643 (0800 CHEMHELP) (NZ use only)

New Zealand National Poisons

Centre

0800 764 766 National Poison Centre

Section 2. Hazards identification

HSNO Classification REPRODUCTIVE TOXICITY - Category 2

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

GHS label elements

Signal word Warning

Hazard statements Suspected of damaging fertility or the unborn child.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid release to the environment.

Response IF exposed or concerned: Get medical attention.

Storage Store locked up.

Disposal Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Symbol

Other hazards which do not result in classification

Defatting to the skin.

Product nameCastrol Transmax Manual FE 75W Product code 469681-DE01 Page: 1/16

Version 4.03 Date of issue 3 July 2024 Format New Zealand Language ENGLISH

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Synthetic base stock. Proprietary performance additives.

| Ingredient name | % (w/w) | CAS number |
|--|-----------|-------------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | ≥60 - ≤75 | 72623-87-1 |
| Dec-1-ene, homopolymer, hydrogenated | ≥10 - ≤30 | 68037-01-4 |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | ≥10 - ≤30 | 68037-01-4 |
| Distillates (petroleum), hydrotreated heavy paraffinic | ≤3 | 64742-54-7 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ≤3 | 64742-65-0 |
| Distillates (petroleum), solvent-refined heavy paraffinic | ≤3 | 64741-88-4 |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | <1 | 192268-65-8 |
| zinc isodecyl phosphorodithioate | ≤0.3 | 25103-54-2 |
| 2,6-di-tert-butylphenol | ≤0.3 | 128-39-2 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation If inhaled, remove to fresh air. Get medical attention.

Do not induce vomiting unless directed to do so by medical personnel. Never give Ingestion

anything by mouth to an unconscious person. If unconscious, place in recovery

position and get medical attention immediately. Get medical attention.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes Skin contact

> while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention. If skin irritation or rash

occurs: Get medical advice/attention.

In case of contact, immediately flush eyes with plenty of water for at least 15 **Eye contact**

minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing.

Check for and remove any contact lenses. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

Suitable Use foam or all-purpose dry chemical to extinguish.

Not suitable Do not use water jet.

Specific hazards arising

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure from the chemical

increase will occur and the container may burst. This material is harmful to aquatic

life with long lasting effects.

Hazardous combustion Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide) products

Hazchem code Not available.

Product nameCastrol Transmax Manual FE 75W Product code 469681-DE01 Page: 2/16

Version 4.03 Date of issue 3 July 2024 **Format New Zealand** Language ENGLISH

Section 5. Firefighting measures

Special precautions for firefighters No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/ containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Contamination

Not suitable Prolonged exposure to elevated temperature

Product nameCastrol Transmax Manual FE 75W

Version 4.03 Date of issue 3 July 2024

Product code 469681-DE01 Page: 3/16

Format New Zealand Language ENGLISH

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|--|---|
| ☑ubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand). [Oil mineral] WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist |
| Distillates (petroleum), hydrotreated heavy paraffinic | HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand). [Oil mineral] WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand). [Oil mineral] WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist |
| Distillates (petroleum), solvent-refined heavy paraffinic | HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand). [Oil mineral] WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist |

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

Appropriate engineering controls

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Product name Castrol Transmax Manual FE 75W

Product code 469681-DE01 Page: 4/16

Version 4.03 Date of issue 3 July 2024 Format New Zealand

Language ENGLISH

Section 8. Exposure controls/personal protection

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

Eye protection Safety glasses with side shields.

Hand protection Wear protective gloves if prolonged or repeated contact is likely. Wear chemical

resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the

working conditions.

Skin protection Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state Liquid.
Colour Brown.

Odour

PH

Not available.

Not applicable.

Not available.

Not available.

Not available.

Not available.

Drop Point Not available.

Flash point Open cup: >220°C (>428°F) [Cleveland ASTM D 92]

Auto-ignition temperature Ingredient name

| Ingredient name | °C | °F | Method |
|---|------------|----------------|-------------|
| Dec-1-ene, homopolymer, hydrogenated | 343 to 369 | 649.4 to 696.2 | ASTM D 2159 |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | 343 to 369 | 649.4 to 696.2 | ASTM D 2159 |

Vapour pressure

Version 4.03

point, and boiling range

| | Vapour Pressure at 20°C | | | Vapo | u <mark>r press</mark> ı | ire at 50°C |
|--|-------------------------|----------|-------------------|----------|--------------------------|-------------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| ubricating oils (petroleum), C20-50, hydrotreated neutral oilbased | <0.07501 | <0.01 | ASTM D 5191 | | | |
| Dec-1-ene, homopolymer, hydrogenated | <0.0041 | <0.00055 | ASTM E 1194-87 | | | |
| Distillates (petroleum), hydrotreated heavy paraffinic | <0.07501 | <0.01 | ASTM D 5191 | | | |

Product nameCastrol Transmax Manual FE 75W

Date of issue 3 July 2024

Format New Zealand Language ENGLISH

Product code 469681-DE01

(ENGLISH)

Page: 5/16

Section 9. Physical and chemical properties

Distillates (petroleum), < 0.07501 ASTM D 5191 solvent-dewaxed heavy paraffinic <0.07501 <0.01 Distillates (petroleum), **ASTM D 5191** solvent-refined heavy paraffinic

Relative vapour density Not available.

<1000 kg/m³ (<1 g/cm³) at 15°C **Density**

Solubility(ies)

| Media | Result |
|-------|-------------|
| water | Not soluble |

Kinematic: 32.2 mm²/s (32.2 cSt) at 40°C **Viscosity**

Kinematic: 6.3 to 6.8 mm²/s (6.3 to 6.8 cSt) at 100°C (ASTM D 445)

Particle characteristics

Median particle size Not applicable.

Section 10. Stability and reactivity

Chemical stability The product is stable.

Under normal conditions of storage and use, hazardous reactions will not occur. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous polymerisation will not

occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

should not be produced. products

Section 11. Toxicological information

Information on likely routes of exposure

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Ingestion No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from

thermal decomposition products occurs.

Ingestion Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact Adverse symptoms may include the following:

> irritation dryness cracking

reduced foetal weight increase in foetal deaths skeletal malformations

Eye contact No specific data.

Acute toxicity

Product nameCastrol Transmax Manual FE 75W Product code 469681-DE01 Page: 6/16

Version 4.03 Date of issue 3 July 2024 **Format New Zealand** Language ENGLISH

| Product/ingredient name | Test | Species | Result | Exposure | Remarks |
|---|------------------------------------|---------|-------------|----------------|--|
| ubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | LC50 Inhalation Dusts and mists | Rat | >5 mg/l | 4 hours | Based on studies with similar substances. |
| | LD50 Dermal | Rat | >5000 mg/kg | - | Based on studies with similar substances. |
| | LD50 Oral | Rat | >5000 mg/kg | - | Based on studies with similar substances. |
| Dec-1-ene, homopolymer, hydrogenated Dec- 1-ene, oligomers, hydrogenated | LD50 Dermal | Rat | >2000 mg/kg | - | Based on studies with similar substances. |
| | LD50 Oral | Rat | >2000 mg/kg | - | - |
| Distillates (petroleum), hydrotreated heavy paraffinic | LD50 Dermal | Rabbit | >5000 mg/kg | - | Based on studies with similar substances. |
| | LD50 Oral | Rat | >5000 mg/kg | - | Based on studies with similar substances. |
| | LD50 Inhalation Dusts and mists | Rat | >5 mg/l | 4 hours | Based on studies with similar substances. |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | LC50 Inhalation Dusts and mists | Rat | >5 mg/l | 4 hours | Based on studies with similar substances. |
| | LD50 Dermal | Rat | >2000 mg/kg | - | Based on studies with similar substances. |
| | LD50 Oral | Rat | >5000 mg/kg | - | Based on studies with similar substances. |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | LD50 Dermal | Rabbit | >2000 mg/kg | - | - |
| | LD50 Oral | Rat | >2000 mg/kg | - | - |
| zinc isodecyl phosphorodithioate | LD50 Dermal | Rat | >5000 mg/kg | - | Based on studies with similar substances. |
| Product nameCastrol Tran | omay Manual EE 75 | ١٨/ | Droduct oc | de 469681-DF01 | Page: 7/16 |

Product nameCastrol Transmax Manual FE 75W

Product code 469681-DE01

Page: 7/16

Version 4.03 Date of issue 3 July 2024

Format New Zealand

Language ENGLISH

| | LD50 Oral | Rat | 3100 mg/kg | - | Based on studies with similar substances. |
|-------------------------|-------------|--------|-------------|---|--|
| 2,6-di-tert-butylphenol | LD50 Dermal | Rabbit | >5000 mg/kg | - | - |
| | LD50 Oral | Rat | >5000 mg/kg | - | - |

Conclusion/Summary

Not available.

Irritation/Corrosion

| Product/ingredient name | Species | Result | Score | Exposure | e Observation | Conc. | Remarks |
|---|-------------|---|-------|----------|---------------|-------|---|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | Rabbit | Eyes - Severe irritant | - | - | - | - | Based on studies with similar substances. |
| | Rabbit | Skin - Non- irritant to skin. | - | - | - | - | Based on studies with similar substances. |
| Dec-1-ene, homopolymer, hydrogenated Dec- 1-ene, oligomers, hydrogenated | Rabbit | Eyes - Non- irritating to the eyes. | - | - | - | - | Based on studies with similar substances. |
| | Rabbit | Skin - Non- irritant to skin. | - | - | - | - | - |
| Distillates (petroleum), hydrotreated heavy paraffinic | Rabbit | Eyes - Non- irritating to the eyes. | - | - | - | - | Based on studies with similar substances. |
| | Rabbit | Skin - Mild irritant | - | - | - | - | Based on studies with similar substances. |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Rabbit | Eyes - Non- irritating to the eyes. | - | - | - | - | Based on studies with similar substances. |
| | Rabbit | Skin - Non- irritant to skin. | - | - | - | - | Based on studies with similar substances. |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | Rabbit | Eyes - Non- irritating to the eyes. | - | - | - | - | - |
| | Rabbit | Skin - Non- irritant to skin. | - | - | - | - | - |
| zinc isodecyl phosphorodithioate | Unspecified | Eyes - Non- irritating to the eyes. | - | - | - | - | ВСОР |

Product nameCastrol Transmax Manual FE 75W

Product code 469681-DE01

Page: 8/16

Version 4.03 Date of issue 3 July 2024

Format New Zealand

Language ENGLISH

| | Unspecified | Skin - Non- irritant to skin. | - | - | - | - | RHE |
|-------------------------|-------------|---|---|---|---|---|-----|
| 2,6-di-tert-butylphenol | Rabbit | Eyes - Non- irritating to the eyes. | - | - | - | - | - |
| | Rabbit | Skin - Irritant | - | - | - | - | - |

Sensitisation

| Product/ingredient name | Route of exposure | Species | Result | Remarks |
|---|-------------------|------------|-----------------|---|
| ✓ubricating oils (petroleum), C20-50, hydrotreated neutral oil- based | skin | Guinea pig | Not sensitising | Based on studies with similar substances. |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | skin | Guinea pig | Not sensitising | - |
| Distillates (petroleum), hydrotreated heavy paraffinic | skin | Guinea pig | Not sensitising | Based on studies with similar substances. |
| Distillates (petroleum), solvent- dewaxed heavy paraffinic | skin | Guinea pig | Not sensitising | Based on studies with similar substances. |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | skin | Guinea pig | Not sensitising | - |
| zinc isodecyl phosphorodithioate | skin | Guinea pig | Not sensitising | Based on studies with similar substances. |
| 2,6-di-tert-butylphenol | skin | Guinea pig | Not sensitising | - |

Potential chronic health effects

General No known significant effects or critical hazards.

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Eye contact

No known significant effects or critical hazards.

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

Suspected of damaging the unborn child.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Mutagenicity

Product name Castrol Transmax Manual FE 75W

Format New Zealand

Product code 469681-DE01

Page: 9/16

Version 4.03 Date of issue 3 July 2024

Language ENGLISH

| Product/ingredient name | Test | Experiment | Result | Remarks |
|---|--|---------------------------------------|----------|---|
| ubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | OECD 473 In vitro Mammalian Chromosomal Aberration Test | Experiment: In vitro | Positive | Based on studies with similar substances. |
| | | Subject: Mammal - species unspecified | | |
| | OECD 471 Bacterial Reverse Mutation Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | 1000 | Subject: Bacteria | | oubotanoco. |
| | OECD 476 In vitro Mammalian Cell Gene Mutation Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | | Subject: Mammal - species unspecified | | |
| | OECD 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo | Negative | Based on studies with similar substances. |
| | Microfiduleus Test | Subject: Mammal - species unspecified | | |
| Dec-1-ene, homopolymer, nydrogenated Dec-1-ene, | OECD 471 Bacterial Reverse Mutation | Experiment: In vitro | Negative | Based on studies with similar |
| oligomers, hydrogenated | Test | Subject: Bacteria | | substances. |
| | OECD 473 In vitro Mammalian Chromosomal Aberration Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | Abeliation rest | Subject: Mammal - species unspecified | | |
| | OECD 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo | Negative | Based on studies with similar substances. |
| | Wild of dollars | Subject: Mammal - species unspecified | | |
| Distillates (petroleum), hydrotreated heavy paraffinic | | Experiment: In vitro | Negative | Based on studies with similar |
| | Test | Subject: Bacteria | | substances. |
| | 473 In vitro Mammalian Chromosomal | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | Aberration Test | Subject: Mammal - species unspecified | | |
| | 476 In vitro Mammalian Cell Gene Mutation Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | | Subject: Mammal - species unspecified | | |
| | 474 Mammalian Erythrocyte | Experiment: In vivo | Negative | Based on studies with similar |

Version 4.03 Date of issue 3 July 2024

Format New Zealand

Language ENGLISH

| | Section | 11. | Toxico | logical | information |
|--|---------|-----|---------------|---------|-------------|
|--|---------|-----|---------------|---------|-------------|

| | Micronucleus Test | | | substances. |
|---|--|---------------------------------------|----------------------|---|
| | | Subject: Mammal - species unspecified | | |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | OECD 471 Bacterial Reverse Mutation Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| paramine | . 551 | Subject: Bacteria | | oubotanooo. |
| | OECD 473 In vitro Mammalian Chromosomal Aberration Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | | Subject: Mammal - species unspecified | | |
| | OECD 476 In vitro Mammalian Cell Gene Mutation Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | | Subject: Unspecified | | |
| | OECD 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo | Negative | Based on studies with similar substances. |
| | | Subject: Mammal - species unspecified | | |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | OECD 471 Bacterial Reverse Mutation Test | Experiment: In vitro | Negative | - |
| | | Subject: Bacteria | | |
| | OECD 473 In vitro Mammalian Chromosomal Aberration Test | Experiment: In vitro | Negative | - |
| | Abeliation rest | Subject: Mammal - species unspecified | | |
| | OECD 476 In vitro Mammalian Cell Gene Mutation Test | Experiment: In vitro | Negative | - |
| | | Subject: Mammal - species unspecified | | |
| zinc isodecyl phosphorodithioate | OECD 471 Bacterial Reverse Mutation Test | Experiment: In vitro | Negative | Based on studies with similar substances. |
| | . 550 | Subject: Bacteria | | Capotarious. |
| | OECD 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo | Negative | Based on studies with similar substances. |
| | | Subject: Mammal - species unspecified | | |
| 2,6-di-tert-butylphenol | OECD 471 Bacterial Reverse Mutation Test | Experiment: In vitro | Negative | - |
| | | Subject: Bacteria | | |
| | OECD 473 In vitro Mammalian | Experiment: In vitro | Negative | - |
| Product nameCastrol Transmax | Manual EE 75W | Drode | uct code 469681-DE01 | Page: 11/16 |

Product name Castrol Transmax Manual FE 75WProduct code 469681-DE01Page: 11/16Version 4.03Date of issue 3 July 2024Format New ZealandLanguage ENGLISH(ENGLISH)

Chromosomal Aberration Test

Subject: Mammal - species unspecified

Teratogenicity

| Product/ingredient name | Test | Species | Result | Exposure |
|---|-----------------|---------|--------|----------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | Negative - Oral | Rat | - | - |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | Positive - Oral | Rat | - | - |

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Developmental toxin | Species | Result | Exposure |
|---|-------------------|-----------|---------------------|---------|--------|----------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | Negative | Negative | Negative | Rat | Oral | - |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | Negative | Negative | Negative | Rat | Oral | - |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | Negative | Negative | Negative | Rat | Oral | - |
| zinc isodecyl phosphorodithioate | Negative | Negative | Negative | Rat | Oral | - |
| 2,6-di-tert-butylphenol | Positive | Negative | Equivocal | Rat | Oral | - |

Aspiration hazard

Name

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Dec-1-ene, homopolymer, hydrogenated

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Section 12. Ecological information

Ecotoxicity

This material is harmful to aquatic life with long lasting effects.

Aquatic and terrestrial toxicity

| Product/ingredient name | Species | Result/Test | Exposure | Effects | Remarks |
|--|---------|---------------------------|----------|---------|---|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | Daphnia | Acute EL50 >10000 mg/l | 48 hours | - | Based on studies with similar substances. |
| | Fish | Acute LL50 >100 mg/l | 96 hours | - | Based on studies with similar substances. |
| | Algae | Acute NOEL ≥100 mg/l | 72 hours | - | - |

Product nameCastrol Transmax Manual FE 75W

Product code 469681-DE01

Page: 12/16

Version 4.03 Date of issue 3 July 2024

Format New Zealand

Language ENGLISH

| | Daphnia | Chronic NOEL | 21 days | - | Based on |
|--|---------|----------------------------------|----------|---|---|
| | Dapinia | ≥1000 mg/l | 2. days | | studies with similar substances |
| Dec-1-ene, nomopolymer, nydrogenated Dec- 1-ene, oligomers, nydrogenated | Algae | Acute EL50 >1000 mg/l | 72 hours | - | Based on studies with similar substances |
| | Daphnia | Acute EL50 >1000 mg/l | 48 hours | - | Based on studies with similar substances. |
| | Fish | Acute LL50 >1000 mg/l | 96 hours | - | - |
| | Daphnia | Chronic NOELR 125 mg/l | 21 days | - | Based on studies with similar substances |
| Distillates (petroleum), nydrotreated heavy paraffinic | Daphnia | Acute EL50 >10000 mg/l | 48 hours | - | - |
| | Fish | Acute LL50 >100 mg/l | 96 hours | - | - |
| | Algae | Chronic NOEL ≥100 mg/l | 72 hours | - | Based on studies with similar substances |
| | Daphnia | Chronic NOEL 10 mg/l | 21 days | - | Based on studies with similar substances |
| Distillates (petroleum), solvent-dewaxed neavy paraffinic | Daphnia | Acute EL50 >1000 mg/l | 48 hours | - | Based on studies with similar substances |
| | Algae | Acute ErL50 100 mg/l | 72 hours | - | Based on studies with similar substances |
| | Fish | Acute LL50 >100 mg/l | 96 hours | - | Based on studies with similar substances |
| | Algae | Chronic NOELR 100 mg/l | 72 hours | - | Based on studies with similar substances |
| | Daphnia | Chronic NOELR 10 to 1000 mg/l | 21 days | - | Based on studies with similar substances |

Product nameCastrol Transmax Manual FE 75W

Product code 469681-DE01

Language ENGLISH

Version 4.03 Date of issue 3 July 2024

Format New Zealand

Page: 13/16

Section 12. Ecological information reaction mass of: Algae Acute EC50 72 hours - -

| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | Algae | Acute EC50 >100 mg/l | 72 hours | - | - |
|---|---------|-----------------------------|----------|---|---|
| | Daphnia | Acute EC50 >100 mg/l | 48 hours | - | - |
| | Fish | Acute LC50 >100 mg/l | 96 hours | - | - |
| | Algae | Chronic NOEC >100 mg/l | 72 hours | - | - |
| | Daphnia | Chronic NOEC 0.026 mg/l | 21 days | - | - |
| | Fish | Chronic NOEC 0.0044 mg/l | 87 days | - | - |
| zinc isodecyl phosphorodithioate | Daphnia | Acute EC50 0.2 mg/l | 48 hours | - | - |
| | Algae | Acute ErC50 >1.6 mg/l | 72 hours | - | - |
| | Fish | Acute LC50 >0.28 mg/l | 96 hours | - | - |
| 2,6-di-tert-butylphenol | Algae | Acute EL50 1.2 mg/l | 96 hours | - | - |
| | Daphnia | Acute EL50 0.45 mg/l | 48 hours | - | - |
| | Fish | Acute LC50 1.4 mg/l | 96 hours | - | - |
| | Algae | Chronic NOEC 0.64 mg/l | 96 hours | - | - |
| | Daphnia | Chronic NOEC 0.035 mg/l | 21 days | - | - |

Persistence and degradability

Partially biodegradable.

| Product/ingredient name | Test | Result | Remarks |
|---|-----------|------------------------------|---|
| ☑ubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | OECD 301F | 31 % - Inherent - 28 days | Based on studies with similar substances. |
| Distillates (petroleum), hydrotreated heavy paraffinic | OECD 301F | 31 % - Not readily - 28 days | Based on studies with similar substances. |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | OECD 301D | 0 % - Not readily - 28 days | - |
| zinc isodecyl phosphorodithioate | OECD 301b | 1 % - Not readily - 28 days | Based on studies with similar substances. |
| 2,6-di-tert-butylphenol | OECD 301B | 24 % - Not readily - 28 days | - |

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

| Product nameCastrol | ransmax Manual FE 75W | nual FE 75W Product code 469681-DE01 Page | |
|----------------------|-----------------------|---|------------------|
| Version 4.03 Date of | issue 3 July 2024 | Format New Zealand | Language ENGLISH |
| | | | (ENGLISH) |

| Product/ingredient name | LogPow | BCF | Potential |
|---|------------|-----|-----------|
| D ec-1-ene, homopolymer, hydrogenated | >6.5 | - | High |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | >10 | - | High |
| Distillates (petroleum), solvent-refined heavy paraffinic | 3.9 to 6 | - | High |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | 4.8 to 8.8 | - | High |
| 2,6-di-tert-butylphenol | 4.5 | - | High |

Mobility in soil

Mobility Spillages may penetrate the soil causing ground water contamination.

Soil/water partition coefficient (Koc)

Not available.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|------------------------|----------------|----------------------|---------|-----|-------|------------------------|
| New Zealand Class | Not regulated. | - | - | - | | - |
| ADG Class | Not regulated. | - | - | - | | - |
| IATA Class | Not regulated. | - | - | - | | - |
| IMDG Class | Not regulated. | - | - | - | | - |

PG*: Packing group

Section 15. Regulatory information

New Zealand Regulatory Information

HSNO Approval Number HSR002606

HSNO Group Standard Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard)

Group Standard 2020

HSNO Classification REPRODUCTIVE TOXICITY - Category 2

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Regulation according to other foreign laws

Product nameCastrol Transmax Manual FE 75W Product code 469681-DE01 Page: 15/16

Version 4.03 Date of issue 3 July 2024 Format New Zealand Language ENGLISH

Section 15. Regulatory information

REACH StatusThe company, as identified in Section 1, sells this product in the EU in compliance

with the current requirements of REACH.

United States inventory

(TSCA 8b)

All components are active or exempted.

Australia inventory (AIIC) All components are listed or exempted.

Canada inventory status
China inventory (IECSC)
All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.
Korea inventory (KECI)
All components are listed or exempted.

Philippines inventory

(PICCS)

All components are listed or exempted.

Taiwan Chemical All components are listed or exempted.

Substances Inventory (TCSI)

Section 16. Other information

History

Date of issue/Date of

3 July 2024

revision

Date of previous issue

26 April 2024.

Version 4.03

Prepared by Not available.

Key to abbreviations Varies = may contain one or more of the following 64741-88-4, 64741-89-5,

64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

Notice to reader

Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameCastrol Transmax Manual FE 75W

Date of issue 3 July 2024

Version 4.03

Format New Zealand

Product code 469681-DE01

Language ENGLISH

(ENGLISH)

Page: 16/16