# SAFETY DATA SHEET



#### Castrol Transmax Universal LL 75W-90

### **Section 1. Identification**

Product name	Castrol Transmax Universal LL 75W-90
Product code	469709-AU22
SDS no.	469709
Use of the substance/mixture	Transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Product type	Liquid.
Supplier	Castrol New Zealand Limited 73 Remuera Road Newmarket Auckland, New Zealand
	www.castrol.com/nz Technical Helpline 0800 10 40 60
Emergency telephone number	0800 243643 (0800 CHEMHELP) (NZ use only)
New Zealand National Poisons Centre	0800 764 766 National Poison Centre

### Section 2. Hazards identification

**HSNO Classification** 

Not classified.

This material is not classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Routes of entry	Dermal contact. Eye contact. Inhalation.
GHS label elements	
Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
Precautionary statements	
Prevention	Read label before use. Keep out of reach of children. If medical advice is needed: Have product container or label at hand.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Other hazards which do not result in classification	Defatting to the skin.

### Section 3. Composition/information on ingredients

Substance/mixture Mixture

Synthetic base stock. Proprietary performance additives.

Version 1.01 Date of issue 18 August 2023

### Section 3. Composition/information on ingredients

Ingredient name	% (w/w)	CAS number
Sec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	≥30 - ≤60	68037-01-4
Polysulfides, di-tert-Bu	≤4.6	68937-96-2
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	≤2	91745-46-9
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	≤3	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	≤3	64742-56-9
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	64742-65-0
O,O,O-Triphenyl phosphorothioate	≤1	597-82-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary first a	aid measures
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Check for and remove any contact lenses. Eyelids should be held away from the eyeball to ensure thorough rinsing. Get medical attention.
Indication of immediate medica	al attention and special treatment needed, if necessary
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

# Section 5. Firefighting measures

Extinguishing media	
Suitable	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Not suitable	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
Hazchem code	Not available.
Special precautions for fire- fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protectiv	ve equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment (see Section 8).
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for conta	ainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor.

### Section 7. Handling and storage

Precautions for safe handling	Put on appropriate personal protective equipment (see Section 8). Wash thoroughly after handling. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated clothing and protective equipment before entering eating areas. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
Not suitable	Prolonged exposure to elevated temperature

### Section 8. Exposure controls/personal protection

#### Control parameters

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	NZ HSWA 2015 - GRWM 2016 (New Zealand). WES-TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Distillates (petroleum), hydrotreated light paraffinic	NZ HSWA 2015 - GRWM 2016 (New Zealand). WES-TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Distillates (petroleum), solvent-dewaxed light paraffinic	NZ HSWA 2015 - GRWM 2016 (New Zealand). WES-TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/
Product nameCastrol Transmax Universal LL 75W-90	Product code 469709-AU22 Page: 3/8
Version 1.01 Date of issue 18 August 2023	Format New Zealand Language ENGLISH
	(ENGLISH)

# Section 8. Exposure controls/personal protection

	Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	NZ HSWA 2015 - GRWM 2016 (New Zealand). WES-TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/ Revised: 9/2010 Form: Mist

#### **Biological exposure indices**

No exposure indices known.

Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	Safety glasses with side shields.
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Skin protection	Use of protective clothing is good industrial practice. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product name	Castrol Transmax Universal LL 75W-90	Product code 4697	709-AU22	Page: 4/8
Version 1.01	Date of issue 18 August 2023	Format New Zealand	Lang	uage ENGLISH
				(ENGLISH)

### Section 8. Exposure controls/personal protection

**Respiratory protection** 

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/ manufacturer and with a full assessment of the working conditions. Respiratory protection should conform to AS/NZS 1715 and AS/NZS 1716.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Physical state Liquid.   Colour Amber.   Odour Not available.   Ph Not applicable.   Weiting point/freezing point Not available.   Boiling point, initial boiling name Not available.   Drop Point Not available.   Prestore and the point of the prestore at 20°C Vapour pressure at 20°C   Vapour pressure Not available.   Not available. Not available.   Vapour pressure at 20°C Vapour pressure at 20°C   Vapour pressure Not available.   Vapour pressure at 20°C Vapour pressure at 50°C   Ingredient name mm Hg kPa Method   Hg Not available. Not available. Not available.   Relative vapour density Not available. Not available. Not available.   Solubility(ries) Not available. Not available. Not available.   Viscosity Kinematic: 104 mm²/s (104 cSt) at 40°C Kinematic: 14.5 to 15.7 cSt) at 100°C   Particle characteristics Kinematic: 14.5 to 15.7 cSt) at 100°C Kinematic: 14.5 to 15.7 cSt) at 100°C   Particle characteristics Median particle size U	Annonion							
Colour Amber.   Odour Not available.   Odour Not available.   Welting point/freezing point Not available.   Boiling point, initial boiling point/ initial boiling point/ initial boiling point, initial boiling point, initial boiling point initial boiling range Not available.   Drop Point Not available. Not available.   Auto-Ignition temperature Not available. Not available.   Vapour pressure Not available. Ingredient name mm Hg kPa Method   Relative vapour density <1000 kg/m³ (<1 g/cm³) at 15°C	Appearance Diversional state	I tau dal						
Ddour Not available.   bH Not applicable.   Welting point/freezing point Not available.   Boiling point, initial boiling point, initial boiling range Not available.   Drop Point Not available.   Flash point Open cup: >180°C (>356°F) [Cleveland]   Auto-ignition temperature Not available.   Vapour pressure at 20°C Vapour pressure at 50°C   Ingredient name mm Hg kPa Method   mg is a valiable. Not available.   Density Not available.   Solubility(les) Not available.   Not available. <1000 kg/m³ (<1 g/cm³) at 15°C		•						
bH Not applicable.   Wetting point/freezing point Not available.   Boiling point, initial boiling point, and boiling range Not available.   Drop Point Not available.   Flash point Open cup: >180°C (>356°F) [Cleveland]   Auto-ignition temperature Not available.   Vapour pressure Not available.   Vapour pressure Not available.   Not available. Not available.   Relative vapour density Not available.   Density <1000 kg/m³ (<1 g/cm³) at 15°C								
Melting point/freezing point Not available.   Boiling point, initial boiling point, and boiling range Not available.   Drop Point Not available.   Flash point Open cup: >180°C (>356°F) [Cleveland]   Auto-ignition temperature Not available.   Vapour pressure Not available.   Relative vapour density Not available.   Density Not available.   Solubility(ies) Not available.   Not available. <1000 kg/m³ (<1 g/cm³) at 15°C								
Boiling point, initial boiling point, and boiling range Not available.   Drop Point Not available.   Flash point Open cup: >180°C (>356°F) [Cleveland]   Auto-ignition temperature Not available.   Vapour pressure Not available.   Vapour pressure Not available.   Vapour pressure Not available.   Vapour pressure Not available.   Relative vapour density Not available.   Density <1000 kg/m³ (<1 g/cm³) at 15°C	•							
point, and boiling range Not available.   Drop Point Not available.   Flash point Open cup: >180°C (>356°F) [Cleveland]   Auto-ignition temperature Not available.   Vapour pressure Not available.   Relative vapour density Not available.   Consity Not available.   Solubility(ies) Not available.   Not available. <1000 kg/m³ (<1 g/cm³) at 15°C			Not available.					
Flash point Open cup: >180°C (>356°F) [Cleveland]   Auto-ignition temperature Not available.   Vapour pressure Not available.   Vapour pressure Not available.   Ingredient name Imm Hg KPa   Method mm KPa   Method Hg Method   Hg KPa Method   Not available. Not available.   Poensity Not available.   Solubility(les) Not available.   Not available. <1000 kg/m³ (<1 g/cm³) at 15°C	Boiling point, initial boiling point, and boiling range	Not available.						
Auto-ignition temperature Vapour pressure Not available.   Vature Vapour Pressure at 20°C Vapour pressure at 50°C   Ingredient name Mm Hg KPa Method mm kPa Method   Relative vapour density Density Not available. Not available. Not available. Not available.   Solubility(ies) Not available. Not available. Not available. <1000 kg/m³ (<1 g/cm³) at 15°C	Drop Point	Not available.						
Vapour pressure Not available.   Ingredient name Vapour Pressure at 20°C Vapour pressure at 50°C   Ingredient name mm Hg kPa Method mm kPa Method   Relative vapour density Not available.   1 <td>Flash point</td> <td>Open cup: &gt;180°C (</td> <td>&gt;356°F) [</td> <td>Clevelar</td> <th>nd]</th> <td></td> <td></td> <td></td>	Flash point	Open cup: >180°C (	>356°F) [	Clevelar	nd]			
Vapour Pressure at 20°C Vapour pressure at 50°C   Ingredient name mm Hg kPa Method mm Hg Method   Relative vapour density Not available.  1 <	Auto-ignition temperature	Not available.						
Ingredient name Imm Hg KPa Method Imm Hg KPa Method   Relative vapour density Not available.	Vapour pressure	Not available.						
Relative vapour density Not available.   Consity Not available.   Solubility(ies) Not available.   Not available. <1000 kg/m³ (<1 g/cm³) at 15°C   Viscosity Kinematic: 104 mm²/s (104 cSt) at 40°C Kinematic: 14.5 to 15.7 mm²/s (14.5 to 15.7 cSt) at 100°C   Particle characteristics Median particle size   Section 10. Stability and reactivity The product is stable.   Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Not all possible sources of ignition (spark or flame).			Vapou	ur Press	sure at 20°C	Vap	our pres	sure at 50°C
Relative vapour density Not available.   Density Not available.   Solubility(ies) Not available.   Not available. <1000 kg/m³ (<1 g/cm³) at 15°C   Viscosity Kinematic: 104 mm²/s (104 cSt) at 40°C Kinematic: 14.5 to 15.7 cSt) at 100°C   Particle characteristics Kinematic: 14.5 to 15.7 mm²/s (14.5 to 15.7 cSt) at 100°C   Particle characteristics Median particle size   Section 10. Stability and reactivity The product is stable.   Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Void all possible sources of ignition (spark or flame).		Ingredient name	mm Hg	kPa	Method		kPa	Method
Density <1000 kg/m³ (<1 g/cm³) at 15°C   Solubility(ies) Not available.   Viscosity Kinematic: 104 mm²/s (104 cSt) at 40°C Kinematic: 14.5 to 15.7 cSt) at 100°C   Particle characteristics Median particle size   Section 10. Stability and reactivity The product is stable.   Chemical stability The product is stable.   Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.   Conditions to avoid Avoid all possible sources of ignition (spark or flame).								
Density <1000 kg/m³ (<1 g/cm³) at 15°C	Polotivo venour donoitu							
Solubility(ies) Not available. Kinematic: 104 mm²/s (104 cSt) at 40°C Kinematic: 14.5 to 15.7 cSt) at 100°C   Particle characteristics Median particle size Kinematic: 14.5 to 15.7 mm²/s (14.5 to 15.7 cSt) at 100°C   Section 10. Stability and reactivity Chemical stability Possibility of hazardous reactions The product is stable. Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.   Conditions to avoid Avoid all possible sources of ignition (spark or flame).			$(m^3)$ at $15^{\circ}$	°C				
Not available.   Viscosity Kinematic: 104 mm²/s (104 cSt) at 40°C Kinematic: 14.5 to 15.7 cSt) at 100°C   Particle characteristics Median particle size Kinematic: 14.5 to 15.7 mm²/s (14.5 to 15.7 cSt) at 100°C   Section 10. Stability and reactivity The product is stable.   Chemical stability reactions The product is stable.   Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.   Conditions to avoid Avoid all possible sources of ignition (spark or flame).	· · · · · · · · · · · · · · · · · · ·	<1000 kg/iii (<1 g/c	in ) at 15	C				
Kinematic: 14.5 to 15.7 mm²/s (14.5 to 15.7 cSt) at 100°C   Particle characteristics   Median particle size   Section 10. Stability and reactivity   Chemical stability   Possibility of hazardous   reactions   Under normal conditions of storage and use, hazardous reactions will not occur.   Under normal conditions of storage and use, hazardous polymerisation will not occur.   Conditions to avoid Avoid all possible sources of ignition (spark or flame).								
Particle characteristics   Median particle size   Section 10. Stability and reactivity   Chemical stability The product is stable.   Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.   Conditions to avoid Avoid all possible sources of ignition (spark or flame).	Viscosity					100°C		
Chemical stabilityThe product is stable.Possibility of hazardous reactionsUnder normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.Conditions to avoidAvoid all possible sources of ignition (spark or flame).	Particle characteristics Median particle size			·				
Possibility of hazardous reactionsUnder normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.Conditions to avoidAvoid all possible sources of ignition (spark or flame).	Section 10. Stabilit	y and reactivi	ty					
reactionsUnder normal conditions of storage and use, hazardous polymerisation will not occur.Conditions to avoidAvoid all possible sources of ignition (spark or flame).	Chemical stability	The product is stable	e.					
	Possibility of hazardous reactions	Under normal condi	Under normal conditions of storage and use, hazardous polymerisation will not					
	Conditions to avoid	Avoid all possible so	ources of i	gnition (	spark or flame	e).		
	Incompatible materials	•			•		na materi	als.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products should not be produced.

products

### Section 11. Toxicological information

	- 3			
Information on likely routes of exposure				
Inhalation	No known significant effects or critical hazards.			
Ingestion	No known significant effects or critical hazards.			
Skin contact	Defatting to the skin. May cause skin dryness and irritation.			
Eye contact	No known significant effects or critical hazards.			
Symptoms related to the physi	cal, chemical and toxicological characteristics			
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.			
Ingestion	No specific data.			
Skin contact	Adverse symptoms may include the following: irritation dryness cracking			
Eye contact	No specific data.			
Potential chronic health effec	<u>ts</u>			
General	No known significant effects or critical hazards.			
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.			
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.			
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.			
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.			
Carcinogenicity	No known significant effects or critical hazards.			
Mutagenicity	No known significant effects or critical hazards.			
Teratogenicity	No known significant effects or critical hazards.			
<b>Developmental effects</b>	No known significant effects or critical hazards.			
Fertility effects	No known significant effects or critical hazards.			
Aspiration hazard				

#### Name

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	26076.06 mg/kg

### Section 12. Ecological information

#### **Ecotoxicity**

No known significant effects or critical hazards.

#### Persistence and degradability

Not expected to be rapidly degradable.

#### **Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogPow	BCF	Potential
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	>6.5		high
Polysulfides, di-tert-Bu	5.6	-	high

#### Mobility in soil

Product nameCastrol Transmax Universal LL 75W-90Product code 469709-AU22Version 1.01Date of issue 18 August 2023Format New ZealandLa

### Section 12. Ecological information

Mobility	Spillages may penetrate the soil causing ground water contamination.		
Soil/water partition coefficient (Koc)	Not available.		
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms.		

Oxygen transfer could also be impaired.

### Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	•					
Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	Not regulated.	-	-	-		-
ADG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-

PG\* : Packing group

# Section 15. Regulatory information

New Zealand Regulatory Information			
HSNO Approval Number	None assigned.		
HSNO Group Standard	None assigned.		
HSNO Classification	Not classified.		
Regulation according to other foreign laws			
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.		
United States inventory (TSCA 8b)	All components are active or exempted.		
Australia inventory (AIIC)	All components are listed or exempted.		
Canada inventory status	At least one component is not listed in DSL but all such components are listed in NDSL.		
China inventory (IECSC)	All components are listed or exempted.		
Japan inventory (CSCL)	All components are listed or exempted.		
Korea inventory (KECI)	All components are listed or exempted.		
Philippines inventory (PICCS)	All components are listed or exempted.		
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.		

Product code 469709-AU22 **Format New Zealand** 

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	18 August 2023
Date of previous issue	29 January 2021.
Version	1.01
Prepared by	Not available.
Key to abbreviations	Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

#### Notice to reader

#### Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.