SAFETY DATA SHEET



Castrol Transmax Dynadrive Long Life 80W-90

Section 1. Identification

Product name Castrol Transmax Dynadrive Long Life 80W-90

Product code 470386-AU22 **SDS no.** 470386

Use of the substance/mixture Manual transmission fluid

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Product type Liquid.

Supplier Castrol New Zealand Limited

73 Remuera Road Newmarket

Auckland, New Zealand

www.castrol.com/nz

Technical Helpline 0800 10 40 60

Emergency telephone number 0800 243643 (0800 CHEMHELP) (NZ use only)

New Zealand National Poisons

Centre

0800 764 766 National Poison Centre

Section 2. Hazards identification

HSNO Classification Not classified.

This material is not classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Routes of entry Dermal contact. Eye contact. Inhalation.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Read label before use. Keep out of reach of children. If medical advice is needed:

Have product container or label at hand.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Other hazards which do not Defatting to the skin.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture Mixture

refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product nameCastrol Transmax Dynadrive Long Life 80W-90 Product code 470386-AU22 Page: 1/8

Version 1.01 Date of issue 18 August 2023 Format New Zealand Language ENGLISH

Section 3. Composition/information on ingredients

Ingredient name	% (w/w)	CAS number
☑istillates (petroleum), hydrotreated heavy paraffinic	≥30 - ≤60	64742-54-7
Residual oils (petroleum), solvent-dewaxed	≥10 - ≤30	64742-62-7
Residual oils (petroleum), hydrotreated	≥10 - ≤30	64742-57-0
Polysulfides, di-tert-Bu	≤4.6	68937-96-2
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	≤2	91745-46-9
O,O,O-Triphenyl phosphorothioate	≤1	597-82-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

If inhaled, remove to fresh air. Get medical attention if symptoms occur. Inhalation

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical

attention if symptoms occur.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

> Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

In case of contact, immediately flush eyes with plenty of water for at least 15 **Eye contact**

minutes. Check for and remove any contact lenses. Eyelids should be held away

from the eyeball to ensure thorough rinsing. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects. **Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training.

Section 5. Firefighting measures

Extinguishing media

Suitable In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Not suitable Do not use water jet.

Specific hazards arising

from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide) products

Hazchem code Not available.

Special precautions for fire-

fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Special protective

Fire-fighters should wear appropriate protective equipment and self-contained equipment for fire-fighters breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery: use care to avoid falling. Put on appropriate personal protective equipment (see Section 8).

Product name Castrol Transmax Dynadrive Long Life 80W-90 Product code 470386-AU22 Page: 2/8

Format New Zealand Version 1.01 Date of issue 18 August 2023 Language ENGLISH

Section 6. Accidental release measures

information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert

material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Prevent entry into sewers,

water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13).

Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe
handling
Put on appropriate personal protective equipment (see Section 8). Wash thoroughly after handling. Eating, drinking and smoking should be prohibited in areas where

this material is handled, stored and processed. Remove contaminated clothing and protective equipment before entering eating areas. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional

information on hygiene measures.

Conditions for safe storage,

including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use

appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	NZ HSWA 2015 - GRWM 2016 (New Zealand). WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Residual oils (petroleum), solvent-dewaxed	NZ HSWA 2015 - GRWM 2016 (New Zealand). WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Residual oils (petroleum), hydrotreated	NZ HSWA 2015 - GRWM 2016 (New Zealand). WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist

Biological exposure indices

No exposure indices known.

Product nameCastrol Transmax Dynadrive Long Life 80W-90 Product code 470386-AU22 Page: 3/8

Version 1.01 Date of issue 18 August 2023 Format New Zealand Language ENGLISH

Section 8. Exposure controls/personal protection

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Hand protection Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/ manufacturer and with a full assessment of the working conditions. Respiratory protection should conform to AS/NZS 1715 and AS/NZS 1716.

Product name Castrol Transmax Dynadrive Long Life 80W-90

Product code 470386-AU22 Page: 4/8

Language ENGLISH

Version 1.01 Date of issue 18 August 2023

Format New Zealand

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

point, and boiling range

Physical state
Colour
Amber.

Odour
Not available.

PH
Not applicable.

Melting point/freezing point
Boiling point, initial boiling
Not available.

Drop Point Not available.

Flash point Open cup: >165°C (>329°F) [Cleveland]

Auto-ignition temperature Not available.

Vapour pressure Not available.

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method

Relative vapour density Not available.

Density <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)
Not available.

Viscosity Kinematic: 172 mm²/s (172 cSt) at 40°C

Kinematic: 16.5 to 17.3 mm²/s (16.5 to 17.3 cSt) at 100°C

Particle characteristics
Median particle size

Section 10. Stability and reactivity

Chemical stability The product is stable.

Possibility of hazardous
Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not

cour

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materialsReactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

products should not be produced.

Section 11. Toxicological information

Information on likely routes of exposure

InhalationNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from

thermal decomposition products occurs.

Ingestion No specific data.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Product nameCastrol Transmax Dynadrive Long Life 80W-90 Product code 470386-AU22 Page: 5/8

Version 1.01 Date of issue 18 August 2023 Format New Zealand Language ENGLISH

Section 11. Toxicological information

Eye contact No specific data.

Potential chronic health effects

General No known significant effects or critical hazards.

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	29559.56 mg/kg

Section 12. Ecological information

Ecotoxicity

No known significant effects or critical hazards.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogPow	BCF	Potential
Polysulfides, di-tert-Bu	5.6	-	high

Mobility in soil

Mobility Spillages may penetrate the soil causing ground water contamination.

Soil/water partition coefficient (Koc)

Not available.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms.

Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Product nameCastrol Transmax Dynadrive Long Life 80W-90 Product code 470386-AU22 Page: 6/8

Version 1.01 Date of issue 18 August 2023 Format New Zealand Language ENGLISH

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	Not regulated.	-	-	-		-
ADG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-

PG*: Packing group

Section 15. Regulatory information

New Zealand Regulatory Information

HSNO Approval Number None assigned.
HSNO Group Standard None assigned.
HSNO Classification Not classified.
Regulation according to other foreign laws

REACH Status For the REACH status of this product please consult your company contact, as

identified in Section 1.

United States inventory

(TSCA 8b)

All components are active or exempted.

Australia inventory (AIIC) All components are listed or exempted.

NDSL.

China inventory (IECSC)

Japan inventory (CSCL)

Korea inventory (KECI)

Philippines inventory

All components are listed or exempted.

All components are listed or exempted.

All components are listed or exempted.

(PICCS)

Taiwan Chemical All components are listed or exempted.

Substances Inventory (TCSI)

Section 16. Other information

History

Date of issue/Date of

revision

18 August 2023

Date of previous issue 8 February 2021.

Version 1.01

Prepared by Not available.

Key to abbreviations Varies = may contain one or more of the following 64741-88-4, 64741-89-5,

64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

Notice to reader

✓ Indicates information that has changed from previously issued version.

Product nameCastrol Transmax Dynadrive Long Life 80W-90 Product code 470386-AU22 Page: 7/8

Version 1.01 Date of issue 18 August 2023 Format New Zealand Language ENGLISH

Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameCastrol Transmax Dynadrive Long Life 80W-90

Product code 470386-AU22

Language ENGLISH

(ENGLISH)

Page: 8/8