SAFETY DATA SHEET



Castrol Transmax Axle EPX 80W-90

Section 1. Identification

Product name	Castrol Transmax Axle EPX 80W-90
Product code	469679-AU22
SDS no.	469679
Use of the substance/mixture	Gear lubricant For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Product type	Liquid.
Supplier	Castrol New Zealand Limited 73 Remuera Road Newmarket Auckland, New Zealand
	www.castrol.com/nz Technical Helpline 0800 10 40 60
Emergency telephone number	0800 243643 (0800 CHEMHELP) (NZ use only)
New Zealand National Poisons Centre	0800 764 766 National Poison Centre

Section 2. Hazards identification

HSNO Classification

Not classified.

This material is not classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Routes of entry	Dermal contact. Eye contact. Inhalation.
GHS label elements	
Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
Precautionary statements	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Other hazards which do not result in classification	$\mathbf{\mathcal{D}}$ efatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture Mixture

Version 2

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Date of issue 2 February 2024

Section 3. Composition/information on ingredients

Ingredient name	% (w/w)	CAS number			
Distillates (petroleum), hydrotreated heavy paraffinic	≥60 - ≤75	64742-54-7			
Residual oils (petroleum), solvent-dewaxed	≥10 - ≤30	64742-62-7			
Residual oils (petroleum), hydrotreated	≥10 - ≤30	64742-57-0			
Amines, C12-14-tert-alkyl	≤0.3	68955-53-3			
(Z)-octadec-9-enylamine	≤0.1	112-90-3			

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary firs	<u>t aid measures</u>
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	onot induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Eye contact	case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Indication of immediate med	ical attention and special treatment needed, if necessary
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Protection of first-aiders	\mathbf{N}_{0} action shall be taken involving any personal risk or without suitable training.

Section 5. Firefighting measures

Extinguishing media	
Suitable	🖟 case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Not suitable	Do not use water jet.
Specific hazards arising from the chemical	\mathbf{M} a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: metal oxide/oxides carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
Hazchem code	Not available.
Special precautions for fire- fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency proceduresFor non-emergency
personnelIf specialised clothing is required to deal with the spillage, take note of any
information in Section 8 on suitable and unsuitable materials. See also the
information in "For non-emergency personnel".For emergency respondersEntry into a confined space or poorly ventilated area contaminated with vapour, mist
or fume is extremely hazardous without the correct respiratory protective equipment
and a safe system of work. Wear self-contained breathing apparatus. Wear a
suitable chemical protective suit. Chemical resistant boots. See also the
information in "For non-emergency personnel".

Product nameCastrol Transmax Axle EPX 80W-90		Product code 4696	379-AU22	Page: 2/7
Version 2	Date of issue 2 February 2024	Format New Zealand	Lang	uage ENGLISH
				(ENGLISH)

Section 6. Accidental release measures

Environmental precautions	✓void dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).				
Methods and material for con	tainment and cleaning up				
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.				
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.				

Section 7. Handling and storage

Precautions for safe handling	✓ut on appropriate personal protective equipment (see Section 8).
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
Not suitable	Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
pistillates (petroleum), hydrotreated heavy paraffinic	NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral] WES-TWA: 5 mg/m ³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m ³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Residual oils (petroleum), solvent-dewaxed	NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral] WES-TWA: 5 mg/m ³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m ³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Residual oils (petroleum), hydrotreated	NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral] WES-TWA: 5 mg/m ³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m ³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Product code 469679-AU22

Page: 3/7

Version 2 Date of issue 2 February 2024

Section 8. Exposure controls/personal protection

Appropriate engineering controls	All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	Safety glasses with side shields.
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	The case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Version 2 Date of issue 2 Fe	ebruary 2024	Format New Zealand	Lang	uage ENGLISH
Product nameCastrol Transmax A	xle EPX 80W-90	Product code 4696	679-AU22	Page: 4/7
Auto-ignition temperature	Not available.			
Flash point		(402.8°F) [Pensky-Martens] (>356°F) [Cleveland]		
Drop Point	Not available.			
Boiling point, initial boiling point, and boiling range	Not available.			
Melting point/freezing point	Not available.			
рН	Not applicable.			
Odour	Not available.			
Colour	Amber. [Light]			
Physical state	Liquid.			
<u>Appearance</u>				

Section 9. Physical and chemical properties

Vapour pressure		Vapour Pressure at 20°C				Vap	our pres	sure at 50°C
	Ing	redient name	mm Hg	kPa	Method	mm Hg	kPa	Method
	Pistillates (petroleum), hydrotreated heavy paraffinic Residual oils (petroleum), solvent- dewaxed Residual oils (petroleum), hydrotreated		<0.08	<0.011 <0.011 <0.011	ASTM D 5191 ASTM D 5191 ASTM D 5191			
			<0.08					
			<0.08					
Relative vapour density	Not	available.			•			
Density	<10	00 kg/m³ (<1 g/c	m³) at 15°	C				
Solubility(ies)								
Media		Result						
water	Not soluble							
Viscosity		matic: 134 mm² matic: 13.8 to 1				00°C		
Particle characteristics								
Median particle size	Not applicable.							
Section 10. Stabil	ity an	d reactivi	ty					
Chemical stability	The product is stable.							
Possibility of hazardous reactions	Und	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not						

	occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on likely ro	utes of exposure
Inhalation	∇ apour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.
Symptoms related to th	e physical, chemical and toxicological characteristics
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Ingestion	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Eye contact	No specific data.
Potential chronic heal	th effects
General	No known significant effects or critical hazards.
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Product nameCastrol Trar	nsmax Axle EPX 80W-90 Product code 469679-AU22 Page: 5/7

Section 11. Toxicological information

Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.
Eye contact	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Aspiration hazard	
Name	

Image: Contract of the second sec

Section 12. Ecological information

Ecotoxicity

No known significant effects or critical hazards.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogPow	BCF	Potential
interview with the set of the se	2.9 4.33	-	low high

Mobility in soil Mobility Soil/water partition coefficient (Koc)

Spillages may penetrate the soil causing ground water contamination. Not available.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	-					
Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	Not regulated.	-	-	-		-
ADG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-

Product nameCastrol Transmax Axle EPX 80W-90

Product code 469679-AU22

Format New Zealand

PG* : Packing group

Section 15. Regulatory information

New Zealand Regulatory Information HSNO Approval Number HSR002606 **HSNO Group Standard** Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2020 **HSNO Classification** Not classified. **Regulation according to other foreign laws REACH Status** For the REACH status of this product please consult your company contact, as identified in Section 1. **United States inventory** All components are active or exempted. (TSCA 8b) Australia inventory (AIIC) All components are listed or exempted. **Canada inventory status** All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (CSCL) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** All components are listed or exempted. (PICCS) **Taiwan Chemical** All components are listed or exempted. Substances Inventory (TCSI)

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	2 February 2024
Date of previous issue	18 August 2023.
Version	2
Prepared by	Not available.
Key to abbreviations	Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Notice to reader

✓ Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.