### SAFETY DATA SHEET



#### Castrol Transmax Limited Slip 80W-90

### Section 1. Identification

Product name Castrol Transmax Limited Slip 80W-90

Product code 469801-MY01

**SDS no.** 469801

Use of the substance/mixture Gear lubricant

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Product type Liquid.

Supplier Castrol New Zealand Limited

73 Remuera Road Newmarket

Auckland, New Zealand

www.castrol.com/nz

Technical Helpline 0800 10 40 60

Emergency telephone number 0800 243643 (0800 CHEMHELP) (NZ use only)

**New Zealand National Poisons** 

Centre

0800 764 766 National Poison Centre

### Section 2. Hazards identification

HSNO Classification ONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Routes of entry Dermal contact. Eye contact. Inhalation.

**GHS label elements** 

Signal word No signal word.

Hazard statements Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** Avoid release to the environment.

Response Not applicable.

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do not

result in classification

Defatting to the skin.

## Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product nameCastrol Transmax Limited Slip 80W-90 Product code 469801-MY01 Page: 1/8

Version 3 Date of issue 5 February 2024 Format New Zealand Language ENGLISH

## Section 3. Composition/information on ingredients

Ingredient name	% (w/w)	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	≥60 - ≤75	64742-54-7
Residual oils (petroleum), solvent-dewaxed	≥10 - ≤30	64742-62-7
Residual oils (petroleum), hydrotreated	≥10 - ≤30	64742-57-0
(Z)-octadec-9-enylamine	≤0.23	112-90-3
Amines, C12-14-tert-alkyl	≤0.16	68955-53-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Do not induce vomiting unless directed to do so by medical personnel. Never give Ingestion

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse

health effects persist or are severe.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

> Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

r case of contact, immediately flush eyes with plenty of water for at least 15 **Eye contact** 

minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing.

Check for and remove any contact lenses. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects. **Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training.

## Section 5. Firefighting measures

**Extinguishing media** 

**Suitable** Use foam or all-purpose dry chemical to extinguish.

Not suitable Do not use water jet.

Specific hazards arising

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure from the chemical increase will occur and the container may burst. This material is harmful to aquatic

life with long lasting effects.

combustion products may include the following: **Hazardous combustion** 

metal oxide/oxides products

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

Hazchem code Not available.

Special precautions for fire-No action shall be taken involving any personal risk or without suitable training. fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if

Product code 469801-MY01

there is a fire.

Special protective Fire-fighters should wear positive pressure self-contained breathing apparatus

equipment for fire-fighters (SCBA) and full turnout gear.

Product name Castrol Transmax Limited Slip 80W-90

Version 3 Date of issue 5 February 2024 **Format New Zealand** Language ENGLISH

(ENGLISH)

Page: 2/8

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Kvoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and material for containment and cleaning up

**Small spill** 

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

Precautions for safe handling

Fut on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

#### Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Stillates (petroleum), hydrotreated heavy paraffinic	NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral] WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist
Residual oils (petroleum), solvent-dewaxed	NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral] WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/

Product nameCastrol Transmax Limited Slip 80W-90

Format New Zealand Language

Product code 469801-MY01

Version 3 Date of issue 5 February 2024 Format New

Language ENGLISH

Page: 3/8

## Section 8. Exposure controls/personal protection

Residual oils (petroleum), hydrotreated

Revised: 9/2010 Form: Mist

NZ HSWA 2015 - GRWM 2016 (New Zealand). [Oil mineral]

WES-TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/

Revised: 6/2016 Form: Mist

WES-STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/

Revised: 9/2010 Form: Mist

#### **Biological exposure indices**

No exposure indices known.

Recommended monitoring procedures

Appropriate engineering controls

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

**Skin protection** 

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product code 469801-MY01

Product nameCastrol Transmax Limited Slip 80W-90

Format New Zealand

Page: 4/8

Version 3 Date of issue 5 February 2024

Language ENGLISH

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance** 

**Physical state** Liquid.

Colour Brown. [Light] **Odour** Not available. Not applicable. pН Not available. Melting point/freezing point **Boiling point, initial boiling** Not available.

**Drop Point** Not available.

Flash point Closed cup: 220°C (428°F) [Pensky-Martens]

Open cup: >180°C (>356°F) [Cleveland]

**Auto-ignition temperature** 

point, and boiling range

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
instillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Residual oils (petroleum), solvent- dewaxed	<0.08	<0.011	ASTM D 5191			
Residual oils (petroleum), hydrotreated	<0.08	<0.011	ASTM D 5191			

Relative vapour density Not available.

**Density** <1000 kg/m³ (<1 g/cm³) at 15.6°C

Solubility(ies)

Media	Result
water	Not soluble

**Viscosity** Kinematic: 145.5 mm<sup>2</sup>/s (145.5 cSt) at 40°C

Kinematic: 14 to 15 mm<sup>2</sup>/s (14 to 15 cSt) at 100°C

**Particle characteristics** 

Median particle size Not applicable.

## Section 10. Stability and reactivity

**Chemical stability** The product is stable.

Possibility of hazardous Under normal conditions of storage and use, hazardous reactions will not occur. reactions

Under normal conditions of storage and use, hazardous polymerisation will not

occur.

**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

**Hazardous decomposition** Under normal conditions of storage and use, hazardous decomposition products

products

should not be produced.

Product nameCastrol Transmax Limited Slip 80W-90 Product code 469801-MY01 Page: 5/8

**Format New Zealand** Version 3 Date of issue 5 February 2024 Language ENGLISH

## Section 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Mapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

**Ingestion** No known significant effects or critical hazards.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

Eye contact

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from

thermal decomposition products occurs.

Ingestion No specific data.

**Skin contact** Adverse symptoms may include the following:

irritation dryness cracking

Eye contact No specific data.

#### Potential chronic health effects

**General** No known significant effects or critical hazards.

**Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Eye contact

No known significant effects or critical hazards.

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

**Aspiration hazard** 

**Name** 

(Z)-octadec-9-enylamine

## **Section 12. Ecological information**

**Ecotoxicity**This material is harmful to aquatic life with long lasting effects.

#### Persistence and degradability

Expected to be biodegradable.

#### **Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogPow	BCF	Potential
√Z)-octadec-9-enylamine	4.33		high
Amines, C12-14-tert-alkyl	2.9		low

#### **Mobility in soil**

**Mobility** Spillages may penetrate the soil causing ground water contamination.

Soil/water partition coefficient (Koc)

Not available.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms.

Oxygen transfer could also be impaired.

Product nameCastrol Transmax Limited Slip 80W-90 Product code 469801-MY01 Page: 6/8

Version 3 Date of issue 5 February 2024 Format New Zealand Language ENGLISH

## Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	Not regulated.	-	-	-		-
ADG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-

PG\* : Packing group

# Section 15. Regulatory information

**New Zealand Regulatory Information** 

HSNO Approval Number HSR002606

HSNO Group Standard Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard)

Group Standard 2020

HSNO Classification ONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Regulation according to other foreign laws

**REACH Status** For the REACH status of this product please consult your company contact, as

identified in Section 1.

**United States inventory** 

(TSCA 8b)

All components are active or exempted.

Australia inventory (AIIC) All components are listed or exempted.

Canada inventory status
China inventory (IECSC)

Japan inventory (CSCL)

Korea inventory (KECI)

All components are listed or exempted.

All components are listed or exempted.

All components are listed or exempted.

Philippines inventory

(PICCS)

**Version** 3

At least one component is not listed.

**Taiwan Chemical** All components are listed or exempted.

**Substances Inventory (TCSI)** 

Product nameCastrol Transmax Limited Slip 80W-90 Product code 469801-MY01

Date of issue 5 February 2024 Format New Zealand Language ENGLISH

(ENGLISH)

Page: 7/8

### Section 16. Other information

**History** 

Date of issue/Date of 5 February 2024

revision

Date of previous issue 18 August 2023.

Version 3

Prepared by Not available.

**Key to abbreviations** Varies = may contain one or more of the following 64741-88-4, 64741-89-5,

64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

#### **Notice to reader**

#### Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameCastrol Transmax Limited Slip 80W-90

Version 3

Date of issue 5 February 2024 Format New Zealand

Language ENGLISH

Product code 469801-MY01

(ENGLISH)

Page: 8/8