SAFETY DATA SHEET



Iloform TDN 81

Section 1. Identification

Product nameIloform TDN 81Product code450946-AU22

SDS no. 450946

Use of the substance/mixture Metalworking fluid - neat.

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Product type Liquid.

Supplier BP Oil New Zealand Limited Ground floor and 1st floor

Watercare House
73 Remuera Road

Newmarket Auckland New Zealand

Phone 09 969 9300

Emergency telephone number 0800 243643 (0800 CHEMHELP) (NZ use only)

New Zealand National Poisons

Centre

0800 764 766 National Poison Centre

OTHER PRODUCT INFORMATION

Technical Helpline 0800 10 40 60

Section 2. Hazards identification

HSNO Classification 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY - Category C

9.1 - AQUATIC ECOTOXICITY - Category A

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Routes of entry Dermal contact. Eye contact. Inhalation.

GHS label elements

Signal word Warning

Hazard statements May cause harm to breast-fed children.

Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention Obtain special instructions before use. Avoid release to the environment. Avoid

contact during pregnancy/while nursing. Do not eat, drink or smoke when using this

product. Wash hands thoroughly after handling.

Response Collect spillage. IF exposed or concerned: Get medical advice/attention.

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Symbol

*

Product namelloform TDN 81 Product code 450946-AU22 Page: 1/8

Version 1.01 Date of issue 9 October 2020 Format New Zealand Language ENGLISH

Section 2. Hazards identification

Other hazards which do not result in classification

Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture

Highly refined mineral oil and additives

Ingredient name	%	CAS number
Mkanes, C14-17, chloro	50 - 95	85535-85-9
Distillates (petroleum), solvent-dewaxed heavy paraffinic	5 - 10	64742-65-0
Distillates (petroleum), hydrotreated heavy paraffinic	5 - 10	64742-54-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse

health effects persist or are severe.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

> Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

In case of contact, immediately flush eyes with plenty of water for at least 15 **Eye contact**

minutes. Check for and remove any contact lenses. Eyelids should be held away

from the eyeball to ensure thorough rinsing. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

from the chemical

Suitable Use foam or all-purpose dry chemical to extinguish.

Not suitable Do not use water jet.

Swarf fires - Neat metal working oils may fume, thermally decompose or ignite if Specific hazards arising

> they come into contact with red hot swarf. To minimise the generation of red hot swarf ensure that a sufficient flow of oil is correctly directed to the cutting edge of the tool to flood it throughout cutting operations. As an additional precaution swarf should be regularly cleared from the immediate area to prevent the risk of fire. In a fire or if heated, a pressure increase will occur and the container may burst. This

material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being

discharged to any waterway, sewer or drain.

Hazardous combustion Combustion products may include the following: products

halogenated compounds

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Hazchem code Not available.

Special precautions for fire-

fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

Product namelloform TDN 81 Product code 450946-AU22 Page: 2/8

Version 1.01 Date of issue 9 October 2020 **Format New Zealand** Language ENGLISH

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment (see Section 8). Contact emergency personnel.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid breathing vapour or mist. Avoid exposure while nursing. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Wash thoroughly after handling. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated clothing and protective equipment before entering eating areas. Workers should wash hands and face before eating, drinking and smoking. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid, as can bacteria, and as a result may induce allergic and other skin reactions, especially if personal hygiene is inadequate.

Conditions for safe storage, including any incompatibilities

Concentrations of mist, fumes and vapours in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided. See also Section 8 for additional information on hygiene measures. Store in accordance with local regulations. Store in original container protected from direct suplight in a dry cool and well-ventilated area, away from incompatible

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Product namelloform TDN 81 Product code 450946-AU22 Page: 3/8

Version 1.01 Date of issue 9 October 2020 Format New Zealand Language ENGLISH

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits		
▶ istillates (petroleum), solvent-dewaxed heavy paraffinic	NZ HSWA 2015 (New Zealand). WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist		
Distillates (petroleum), hydrotreated heavy paraffinic	NZ HSWA 2015 (New Zealand). WES-TWA: 5 mg/m³ 8 hours. Issued/ Revised: 6/2016 Form: Mist WES-STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 9/2010 Form: Mist		

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product namelloform TDN 81 Product code 450946-AU22 Page: 4/8

Version 1.01 Date of issue 9 October 2020 Format New Zealand Language ENGLISH

Section 8. Exposure controls/personal protection

Skin protection Use of protective clothing is good industrial practice. Cotton or polyester/cotton

> overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. The correct

choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/ manufacturer and with a full assessment of the working conditions. Respiratory

protection should conform to AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance

Physical state Liquid. Colour Amber. **Odour** Not available. pН Not available. **Melting point** Not available. **Boiling point** Not available. **Drop Point** Not available.

Closed cup: 208°C (406.4°F) [Pensky-Martens.] Flash point

Vapour pressure Not available. Vapour density Not available.

>1000 kg/m3 (>1 g/cm3) at 15°C **Density**

Solubility insoluble in water.

Viscosity Kinematic: 140 mm²/s (140 cSt) at 40°C

Section 10. Stability and reactivity

Chemical stability The product is stable.

Possibility of hazardous

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not reactions

Conditions to avoid Avoid excessive heat.

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

products should not be produced.

Section 11. Toxicological information

Information on likely routes of exposure

Inhalation No known significant effects or critical hazards. Ingestion No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics

Inhalation Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Product namelloform TDN 81 Product code 450946-AU22 Page: 5/8

Version 1.01 Date of issue 9 October 2020 **Format New Zealand** Language ENGLISH

Section 11. Toxicological information

Ingestion Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

reduced foetal weight increase in foetal deaths skeletal malformations

Eye contact No specific data.

Potential chronic health effects

General No known significant effects or critical hazards.

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.

Developmental effects May cause harm to breast-fed children.

Fertility effects No known significant effects or critical hazards.

Section 12. Ecological information

Ecotoxicity

Water polluting material. May be harmful to the environment if released in large quantities. This material is very toxic to aquatic life with long lasting effects.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

Not available.

Product/ingredient name	LogPow	BCF	Potential
Alkanes, C14-17, chloro	4.7 to 8.3	-	high

Mobility in soil

Mobility Non-volatile. Liquid. insoluble in water.

Soil/water partition Not available.

coefficient (Koc)

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Product namelloform TDN 81 Product code 450946-AU22 Page: 6/8

Version 1.01 Date of issue 9 October 2020 Format New Zealand Language ENGLISH

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	UN3082	Environmentally hazardous substance, liquid, n.o.s Marine pollutant (Alkanes, C14-17, chloro)	9	III	Water State	Hazchem code •3Z
ADG Class	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Alkanes, C14-17, chloro)	9	III	***************************************	The product is not regulated as a dangerous good when transported by road or rail in either an IBC, or in other container types if ≤500 kg. This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Hazchem code •3Z
IATA Class	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Alkanes, C14-17, chloro)	9	III	***************************************	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
IMDG Class	UN3082	Environmentally hazardous substance, liquid, n.o.s Marine pollutant (Alkanes, C14-17, chloro)	9	III	***	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F

PG* : Packing group

Section 15. Regulatory information

New Zealand Regulatory Information

HSNO Approval Number HSR002606

HSNO Group Standard Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary

Hazard) Group Standard 2006

HSNO Classification 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY - Category C

9.1 - AQUATIC ECOTOXICITY - Category A

Regulation according to other foreign laws

REACH Status For the REACH status of this product please consult your company contact, as

identified in Section 1.

United States inventory

(TSCA 8b)

Not determined.

Australia inventory (AICS)
Canada inventory status
China inventory (IECSC)
Japan inventory (ENCS)
Korea inventory (KECI)
All components are listed or exempted.

(PICCS)

All compenents are listed or exempted.

Taiwan Chemical All components are listed or exempted.

Substances Inventory (TCSI)

Section 16. Other information

History

Date of issue/Date of

revision

9 October 2020

Date of previous issue 30 October 2019.

Version 1.01

Prepared by Not available.

Key to abbreviations Varies = may contain one or more of the following 64741-88-4, 64741-89-5,

64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

Notice to reader

Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product namelloform TDN 81 Product code 450946-AU22 Page: 8/8

Version 1.01 Date of issue 9 October 2020 Format New Zealand Language ENGLISH