# TRIM

# SAFETY DATA SHEET

**Section 1: Identification** 

Product identifier TRIM® E715

Other means of identification None.

Recommended use of the chemical and restrictions on use

Recommended use Metal working fluids

**Restrictions on use** Applicable for industrial settings only. No other uses are advised.

Details of manufacturer or importer

Supplier

Company name Industrial Lubricants & Services Ltd

Address 15 Accent Drive

East Tamaki 2013

Auckland New Zealand

**Telephone** 64 9 2740159

ManufacturerMaster Fluid Solutions (India) Pvt. Ltd.AddressB-41, Chakan Industrial Area Phase - 2

Pune - 410501 Maharashtra

India

e-mail sales@masterfluidsolutions.com

**Emergency telephone** 

number

0800 10 40 17 ( NZ use only)

NEW ZEALAND NATIONAL

**POISONS CENTRE** 

0800 764 766

#### Section 2: Hazard identification

**HSNO classification** 6.4A - Substances that are irritating to the eye

This material has been classified in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017 and classified as hazardous according to the Hazardous Substances (Classification) Regulations 2001.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2020 Transport of Dangerous Goods on Land.

Routes of exposure Eye contact. Skin contact.

Classification of the hazardous chemical

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2

Environmental hazards Not classified.

Label elements, including precautionary statements

Hazard symbol(s)

**(!)** 

Exclamation mark

Signal word Warning

Hazard statement(s) Causes serious eye irritation.

Precautionary statement(s)

**Prevention** Wash hands thoroughly after handling. Wear eye protection/face protection.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

**Storage** Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

None.

Supplemental information

None.

## Section 3: Composition/information on ingredients

#### **Mixture**

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
SEVERELY HYDROTREATED PETROLEUM OIL	64742-52-5	50 - < 60
AMINE NEUTRALIZED PHOSPHATE ESTERS	Mixture	3 - < 5
HEXYLENE GLYCOL	107-41-5	1 - < 3
TRIMETHYLOLPROPANE POLYOXYPROPYLENE TRIAMINE	39423-51-3	1 - < 3
Other components below reportable levels		40 - < 50

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## Section 4: First-aid measures

#### Description of necessary first aid measures

**Inhalation** Move to fresh air.

**Skin contact** Wash affected area with mild soap and water.

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses.

**Ingestion** In the unlikely event of swallowing contact a physician or poison control centre.

**Notes to physician** Provide general supportive measures and treat symptomatically.

Personal protection for first-aid

responders

In the case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

## Section 5: Fire-fighting measures

## **Extinguishing media**

Suitable extinguishing

media

Dry chemical, CO2, water spray or alcohol resistant foam. Use fire-extinguishing media

appropriate for surrounding materials.

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from

the chemical

No unusual fire or explosion hazards noted.

**Hazardous combustion** 

products

Combustion products may contain oxides of: Carbon (COx) Nitrogen (NOx) Phosphorus

Special protective equipment and precautions for firefighters

Wear suitable protective equipment. Use standard firefighting procedures and consider the

hazards of other involved materials.

### Section 6: Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. For personal protection, see section 8. Use personal

protective equipment as required.

For emergency responders Use personal protective equipment as required.

**Environmental precautions** 

Prevent entry into waterways, sewer, basements or confined areas.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material. Clean up in accordance with all applicable regulations.

#### Section 7: Handling and storage

Precautions for safe handling

Do not taste or swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin.

Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store in a closed container. The product is stable and non-reactive under normal conditions of use,

storage and transport. Store in a dry place.

## Section 8: Exposure controls/personal protection

#### **Control parameters**

## Occupational exposure limits

Components	lace Exposure Standards) Type	Value	Form
HEXYLENE GLYCOL (CAS 107-41-5)	Ceiling	121 mg/m3	
		25 ppm	
SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
US. ACGIH Threshold Limit			<b></b>
Components	Туре	Value	Form
HEXYLENE GLYCOL (CAS 107-41-5)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
UK. EH40 Workplace Expos		Value	
Components	Туре	Value	
HEXYLENE GLYCOL (CAS 107-41-5)	STEL	123 mg/m3	
		25 ppm	
	TWA	123 mg/m3	
		25 ppm	
		25 ppm	
Australia. National Workpla Components	ce OELs (Workplace Exposure Stand	• •	ants, Appendix A)
-		dards for Airborne Contamin	ants, Appendix A)
Components HEXYLENE GLYCOL (CAS	Туре	dards for Airborne Contamin Value	ants, Appendix A)
Components  HEXYLENE GLYCOL (CAS 107-41-5)	Туре	dards for Airborne Contamin Value 121 mg/m3 25 ppm	
Components  HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I	<b>Type</b> Ceiling	dards for Airborne Contamin Value 121 mg/m3 25 ppm	
Components  HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment)	Type  Ceiling  National Exposure Standards for Atm	dards for Airborne Contamin Value 121 mg/m3 25 ppm nospheric Contaminants in the	ne Occupational
Components  HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS	Type  Ceiling  National Exposure Standards for Atm  Type	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3	ne Occupational Form
Components  HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5)	Type Ceiling National Exposure Standards for Atm Type TWA	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3  or the ingredient(s). ust ventilation, or other engineer	ne Occupational Form Mist. ering controls to control airbo
Components  HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5)  logical limit values propriate engineering trols	Type  Ceiling  National Exposure Standards for Atm  Type  TWA  No biological exposure limits noted for Use process enclosures, local exhaulevels below recommended exposure.	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3  or the ingredient(s).  ust ventilation, or other engineers in the limits. Eye wash fountain and	ne Occupational Form Mist. ering controls to control airbo
Components  HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5)  logical limit values propriate engineering trols	Type  Ceiling  National Exposure Standards for Atm  Type  TWA  No biological exposure limits noted f Use process enclosures, local exhaulevels below recommended exposure recommended.	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3  or the ingredient(s).  ust ventilation, or other engineers in the limits. Eye wash fountain and	ne Occupational Form Mist. ering controls to control airbo
Components  HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5) logical limit values propriate engineering trols  vidual protection measures	Type Ceiling  National Exposure Standards for Atm Type TWA  No biological exposure limits noted f Use process enclosures, local exhaulevels below recommended exposure recommended.  for example personal protective equations	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3  or the ingredient(s). ust ventilation, or other engineer imits. Eye wash fountain and uipment (PPE)	ne Occupational Form Mist. ering controls to control airbo
HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5) logical limit values propriate engineering trols  vidual protection measures Eye/face protection Skin protection	Type Ceiling  National Exposure Standards for Atm Type TWA  No biological exposure limits noted f Use process enclosures, local exhaulevels below recommended exposure recommended.  for example personal protective equal Safety glasses.  Wear appropriate chemical resistant	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3  or the ingredient(s).  ust ventilation, or other enginese limits. Eye wash fountain and uipment (PPE)	ne Occupational Form Mist. ering controls to control airbo
HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5) logical limit values propriate engineering trols  vidual protection measures. Eye/face protection Skin protection Hand protection Other	Type  Ceiling  National Exposure Standards for Atm  Type  TWA  No biological exposure limits noted f  Use process enclosures, local exhaulevels below recommended exposure recommended.  for example personal protective equal safety glasses.	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3  or the ingredient(s). ust ventilation, or other enginese limits. Eye wash fountain and uipment (PPE)  gloves. clothing.	ne Occupational Form Mist. ering controls to control airbot emergency showers are
HEXYLENE GLYCOL (CAS 107-41-5)  Australia. OELs. (Adopted I Environment) Components  SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-52-5) logical limit values propriate engineering trols  vidual protection measures. Eye/face protection Skin protection Hand protection	Type Ceiling  National Exposure Standards for Atm Type TWA  No biological exposure limits noted f Use process enclosures, local exhaulevels below recommended exposure recommended. If or example personal protective equivalent particular safety glasses.  Wear appropriate chemical resistant wear appropriate chemical resistant	dards for Airborne Contamin Value  121 mg/m3  25 ppm  nospheric Contaminants in the Value  5 mg/m3  or the ingredient(s).  ust ventilation, or other engineers in the limits. Eye wash fountain and uipment (PPE)  gloves. clothing. ar suitable respiratory equipment	ne Occupational Form Mist. ering controls to control airbot emergency showers are

# Section 9: Physical and chemical properties

**Appearance** 

Physical stateLiquid.FormLiquid.

Colour Amber
Odour Mild amine
Odour threshold Not available.

**pH** 9 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point > 160.0 °C (> 320.0 °F)

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Soluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Kinematic viscosity Not available.

Other physical and chemical parameters

Flash point class ASTM D93-08
pH in aqueous solution 8.7 - 9.7
Specific gravity 0.95 - 0.98

Section 10: Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerisation does not occur.

**Conditions to avoid**Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines.

**Incompatible materials** Powerful oxidizers. Strong acids.

Hazardous decomposition

products

To avoid thermal decomposition, do not overheat.

**Section 11: Toxicological information** 

Information on likely routes of exposure

**Inhalation** No adverse effects due to inhalation are expected.

Skin contact Not classified.

**Eye contact** May be irritating to eyes.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May be irritating to eyes.

Acute toxicity Not classified.

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

May be irritating to eyes.

Respiratory sensitisation Not classified.

Skin sensitisation This product is not expected to cause skin sensitisation.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not classified. **Aspiration hazard** 

## Section 12: Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available.

Persistence and degradability

No data is available on the degradability of this product.

Mobility in soil No data available for this product.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## Section 13: Disposal considerations

Disposal methods Dispose of contents/container in accordance with local/regional/national/international regulations.

Residual waste Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Follow precautions for safe handling described in this safety data sheet.

Dispose in accordance with all applicable regulations. Special precautions

Method of disposal that should

Review federal, state/provincial, and local government requirements prior to disposal.

not be used

#### Section 14: Transport information

#### **IATA**

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Not regulated

Annex II of MARPOL 73/78 and

the IBC Code

## Section 15: Regulatory information

**HSNO Approval Number** HSR002606

Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group **HSNO Group Standard** 

Standard 2020

**HSNO** classification 6.4A - Substances that are irritating to the eye

Applicable regulations

## New Zealand Inventory of Chemicals (NZIoC): Registration status

HEXYLENE GLYCOL (CAS 107-41-5) **HSNO** Approved

SEVERELY HYDROTREATED PETROLEUM OIL (CAS

64742-52-5)

May be used as a single component chemical under an

appropriate group standard

TRIMETHYLOLPROPANE POLYOXYPROPYLENE

TRIAMINE (CAS 39423-51-3)

May be used as a component in a product covered by a group standard but it is not approved for use as a chemical in its own

right.

#### International Inventories

Country(s) or region Inventory name On inventory (yes/no)\* New Zealand New Zealand Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

#### Section 16: Other information

Issue date 27-October-2022

Version No. 01

Key abbreviations or acronyms

used

Not available.

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Master Fluid Solutions cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe

in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury,

damage or expense due to improper use.

**Revision information** Composition / Information on Ingredients: Ingredients

HazReg Data: International Inventories

GHS: Classification

Material name: TRIM® E715 SDS NEW ZEALAND

7335 Version #: 01 Issue date: 27-October-2022