

SAFETY DATA SHEET

JAX MAGNA-PLATE 22

Infosafe No.: LQ45E ISSUED Date : 18/12/2019 ISSUED by: Industrial Lubricants & Services

Ltc

1. IDENTIFICATION

GHS Product Identifier

JAX MAGNA-PLATE 22

Company Name

Industrial Lubricants & Services Ltd

Address

PO Box 259 347, Botany, Manukau 2163 Auckland, NEW ZEALAND

Telephone/Fax Number

Tel: 0800 10 40 11 Fax: 0800 10 40 15

Emergency phone number

0800 10 40 17

E-mail Address

orders@industlubes.co.nz

Recommended use of the chemical and restrictions on use

Lubricant.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand. Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

6.3B Substance that is mildly irritating to the skin

6.4A Substance that is irritating to the eyes

6.5B Substance that is a contact sensitiser

9.1B Substance that is ecotoxic in the aquatic environment

Signal Word (s)

WARNING

Hazard Statement (s)

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Exclamation mark, Environment



Precautionary statement - Prevention

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement - Response

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

Precautionary statement - Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6	2.5-<10 %
Sulfonic acids, petroleum, calcium salts	61789-86-4	2.5-<10 %
Calcium Carbonate	471-34-1	0.1-<5 %
Calcium Dodecylbenzene sulphonate	26264-06-2	1-<3 %
Zinc oxide	1314-13-2	0.25-<2.5 %
Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	70024-69-0	0.1-<1 %
Ingredients determined not to be hazardous		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable Extinguishing Media

Water with full jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including metal oxide, sulphur oxides, carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising From The Chemical

This product will burn if exposed to fire.

Hazchem Code

•3Z

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Calcium carbonate:

TWA: 10 mg/m³

Zinc oxide

TWA: 3 mg/m³ (fume), 10 mg/m³(dust)

STEL: 10 mg/m³ (fume)

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eighthour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Source: Workplace Exposure Standards and Biological Exposure Indices.

Biological Limit Values

No biological limits allocated.

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Paste	Appearance	Paste.
Colour	White	Odour	Aromatic
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	Not available	Solubility in Water	Insoluble.
Specific Gravity	0.95-1.05	pH	Not available
Vapour Pressure	Not available	Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Flash Point	> 180°C
Flammability	Not flammable	Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available	Flammable Limits - Upper	Not available
Explosion Properties	Product does not present an explosion hazard.		

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling.

Reactivity and Stability

Reacts with incompatible materials

Conditions to Avoid

Heat, open flames and other sources of ignition.

Incompatible materials

Avoid strong oxidants, strong alkalis and strong acids.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: sulphur oxides, metal oxide, carbon monoxide, nitrogen oxides and carbon dioxide.

Possibility of hazardous reactions

Not available

Hazardous Polymerization

Not available

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material. The available acute toxicity data for the ingredient/s is/are given below.

Acute Toxicity - Oral

Zinc oxide

LD50 (rat): >5000mg/kg

Sulfonic acids, petroleum, calcium salts LD50 (rat): >5000mg/kg (OECD 401)

Calcium carbonate LD50 (rat): 6,450 mg/kg

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

Causes mild skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis. May cause an allergic skin reaction.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause damage to organs through single exposure.

STOT-repeated exposure

Not expected to cause damage to organs through repeated exposure.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Prevent large amounts from entering waterways, drains and sewers.

Acute Toxicity - Fish

Sulfonic acids, petroleum, calcium salts. LC50(Fish): >10,000 mg/l/96h (OECD 203)

Zinc oxide

LC50(Fish): 0-1 mg/l/96h

Acute Toxicity - Algae

Zinc oxide

IC50(Pseudokirchneriella Subcapitata): 0.17 mg/l/72h

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a combustible substance and therefore can be sent to an approved high temperature incineration plant for disposal.

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. TRANSPORT INFORMATION

Transport Information

This material is classified as a Class 9 – Miscellaneous Substances

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1: Explosives

Class 9 dangerous goods that contain organic matter must not be loaded in the same bulk container or tankwagon with dangerous goods of Division 5.1 unless the Class 9 and Division 5.1 dangerous goods are in separate compartments of a bulk container or tankwagon.

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices. Segregation devices may be used to segregate Dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of Class 3, 4, 5, 6 or 8 or from food items.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 9 UN No: 3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Zinc oxide) (MARINE POLLUTANT)

Packing Group: III EMS: F-A, S-F

Special Provisions: 274, 335, 969

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 9 UN No: 3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Zinc oxide)

Packing Group: III

Packaging Instructions (passenger & cargo): 964

Packaging Instructions (cargo only): 964

Hazard Label: Miscellaneous

Special Provisions: A97, A158, A197

U.N. Number

3082

UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Contains Zinc oxide)

Transport hazard class(es)

9

Packing Group

Ш

Hazchem Code

•3Z

IERG Number

47

IMDG Marine pollutant

Yes

Transport in Bulk

Not available

Special Precautions for User

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

Group Standard:Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2006

HSNO Approval Number

HSR002606

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Reviewed: December 2019 Supersedes: January 2015

References

Workplace Exposure Standards and Biological Exposure Indices.

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Ptv Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.