



MSDS SUPPLEMENT TO GHS REGULATIONS

To comply with the Hazardous Substance and New Organisms Act, this coversheet offers New Zealand specific information. This page "0", is to be considered part of the MSDS.

PRODUCT NAME & COMPANY IDENTIFICATION

Product Name	Date of Issue
AMERICA'S FINEST PENETRATING OIL AEROSOL	1 November 2023

Company Name	INDUSTRIAL LUBRICANTS & SERVICES LTD 1/15 Accent Drive East Tamaki Auckland, 2013 Tel - (+64) 9 274 0159
---------------------	---

Emergency Contact	<u>National Poisons Centre - New Zealand</u> 0800 764 766 or Chemcall 0800 243 622
--------------------------	---

Hazard Identification

According to criteria in the Hazardous Substances (Hazard Classification) Notice 2020, this material is **CLASSIFIED as Hazardous**

GHS 7 or REACH	Flammable Aerosol - Cat 1 Specific target organ toxicity-single exposure - Cat 3 Gases under pressure Compressed gas Narcosis aspiration hazard - Cat 1 Skin corrosion/irritation - Cat 2
-----------------------	--

According to criteria in Transport of Dangerous Goods on Land NZS 5433:2020, product is **CLASSIFIED as Dangerous for transport.**

Other Information

HSN (Tariff Code)	2710.12.59 19B
Shelf Life	5 Years

INDUSTRIAL LUBRICANTS & SERVICES LTD

CS Tel: 0800 104 011

Technical Tel: 0800 104 017

www.ils.co.nz

orders@ils.co.nz

Page 0 of 15

**AMERICA'S FINEST PENETRATING OIL
AEROSOL**

Issue Date: 01/11/2023



JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 11/1/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : JAX America's Finest Penetrating Oil (Aerosol)
Product code : JAX101

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricant where there is no possibility of contact with food

1.3. Supplier

JAX INC.
N59 W13330, Manhardt Dr
Menomonee Falls, WI 53051
T (262) 781-8850
info@jax.com

1.4. Emergency telephone number

Emergency number : Infotrac : North America 1-800-535-5053 | International 1-352-323-3500

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Gases under pressure Compressed gas	H280	Contains gas under pressure; may explode if heated
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P302+P352 - If on skin: Wash with plenty of water.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

83.22% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Gas))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
white mineral oil (petroleum)	CAS-No.: 8042-47-5	25 – 50
naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	15 – 25
n-pentane	CAS-No.: 109-66-0	10 – 15
propane	CAS-No.: 74-98-6	10 – 15
dipropylene glycol monomethyl ether	CAS-No.: 34590-94-8	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after ingestion : Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Do not use a heavy water stream. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

JAX America's Finest Penetrating Oil (Aerosol)	
No additional information available	
propane (74-98-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Propane
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Propane
OSHA PEL TWA [1]	1800 mg/m ³
OSHA PEL TWA [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
n-pentane (109-66-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Pentane
ACGIH OEL TWA [ppm]	1000 ppm 1000 ppm
Remark (ACGIH)	TLV® Basis: Narcosis; resp tract irr
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Pentane
OSHA PEL TWA [1]	2950 mg/m ³
OSHA PEL TWA [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
naphtha (petroleum), hydrotreated light (64742-49-0)	
No additional information available	
dipropylene glycol monomethyl ether (34590-94-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
ACGIH OEL TWA [ppm]	50 ppm

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dipropylene glycol monomethyl ether (34590-94-8)

Remark (ACGIH) : TLV® Basis: Liver & CNS eff

Regulatory reference : ACGIH 2022

USA - OSHA - Occupational Exposure Limits

Local name : Dipropylene glycol methyl ether

OSHA PEL TWA [1] : 600 mg/m³

OSHA PEL TWA [2] : 100 ppm

Regulatory reference (US-OSHA) : OSHA Annotated Table Z-1

white mineral oil (petroleum) (8042-47-5)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA : 5 mg/m³ (Inhalable fraction)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Color : Black
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

JAX America's Finest Penetrating Oil (Aerosol)

Unknown acute toxicity (GHS US)	83.22% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Gas))
---------------------------------	--

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 20 mg/l air (4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	364 mg/l Source: ChemIDplus
ATE US (vapors)	364 mg/l/4h
naphtha (petroleum), hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
ATE US (gases)	73680 ppmV/4h
dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 19020 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	9510 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 3000 mg/m ³ Source: ECHA
ATE US (dermal)	9510 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h
white mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation	: Causes skin irritation.
propane (74-98-6)	
pH	No data available in the literature
n-pentane (109-66-0)	
pH	No data available in the literature
dipropylene glycol monomethyl ether (34590-94-8)	
pH	7 (100 %, 25 °C)
white mineral oil (petroleum) (8042-47-5)	
pH	No data available in the literature
Serious eye damage/irritation	: Not classified

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

propane (74-98-6)	
pH	No data available in the literature
n-pentane (109-66-0)	
pH	No data available in the literature
dipropylene glycol monomethyl ether (34590-94-8)	
pH	7 (100 %, 25 °C)
white mineral oil (petroleum) (8042-47-5)	
pH	No data available in the literature
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
n-pentane (109-66-0)	
STOT-single exposure	May cause drowsiness or dizziness.
naphtha (petroleum), hydrotreated light (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
n-pentane (109-66-0)	
NOAEC (inhalation, rat, vapor, 90 days)	30 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other:, Guideline: EPA OTS 798.2450 (90-Day Inhalation Toxicity), Guideline: other:, Guideline: other:
naphtha (petroleum), hydrotreated light (64742-49-0)	
LOAEC (inhalation, rat, vapor, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
NOAEC (inhalation, rat, vapor, 90 days)	2355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
dipropylene glycol monomethyl ether (34590-94-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: other:
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: No data available
propane (74-98-6)	
Viscosity, kinematic	No data available in the literature
n-pentane (109-66-0)	
Viscosity, kinematic	0.2 – 0.52 mm ² /s (20 °C, ASTM D7042: Dynamic viscosity and density of liquids)
naphtha (petroleum), hydrotreated light (64742-49-0)	
Viscosity, kinematic	< 1 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dipropylene glycol monomethyl ether (34590-94-8)

Viscosity, kinematic 4.55 mm²/s (20 °C, OECD 114: Viscosity of Liquids)

white mineral oil (petroleum) (8042-47-5)

Viscosity, kinematic 3 – 20.5 mm²/s (40 °C, ISO 3104: Determination of kinematic viscosity and calculation of dynamic viscosity, Niet experimenteel bepaald; afgeleid van de indeling)

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after ingestion : Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

propane (74-98-6)

EC50 - Other aquatic organisms [1]

<

EC50 96h - Algae [1]

11.89 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

n-pentane (109-66-0)

LC50 - Fish [1]

4.26 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)

EC50 - Crustacea [1]

2.7 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value)

ErC50 algae

10.7 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, GLP)

dipropylene glycol monomethyl ether (34590-94-8)

LC50 - Fish [1]

> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value, GLP)

EC50 - Other aquatic organisms [1]

1930 mg/l Test organisms (species): other aquatic crustacea:

EC50 72h - Algae [1]

> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

EC50 96h - Algae [1]

> 969 mg/l Source: ECHA

ErC50 algae

> 969 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

LOEC (chronic)

0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

NOEC (chronic)

≥ 0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

white mineral oil (petroleum) (8042-47-5)

LC50 - Fish [1]

> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

propane (74-98-6)

Persistence and degradability Readily biodegradable in water.

n-pentane (109-66-0)

Persistence and degradability Readily biodegradable in water.

dipropylene glycol monomethyl ether (34590-94-8)

Persistence and degradability Readily biodegradable in water.

Biochemical oxygen demand (BOD) 0 g O₂/g substance

ThOD 2.06 g O₂/g substance

white mineral oil (petroleum) (8042-47-5)

Persistence and degradability Not readily biodegradable in water.

12.3. Bioaccumulative potential

propane (74-98-6)

Partition coefficient n-octanol/water (Log Pow) 1.09 – 2.8 (Experimental value, 20 °C)

Bioaccumulative potential Low potential for bioaccumulation (Log Kow < 4).

n-pentane (109-66-0)

Partition coefficient n-octanol/water (Log Pow) 3.45 (Experimental value, 25 °C)

Bioaccumulative potential Low potential for bioaccumulation (Log Kow < 4).

naphtha (petroleum), hydrotreated light (64742-49-0)

Partition coefficient n-octanol/water (Log Pow) 2.1 – 6 Source: IUCLID

dipropylene glycol monomethyl ether (34590-94-8)

Partition coefficient n-octanol/water (Log Pow) 0.004 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)

Bioaccumulative potential Low potential for bioaccumulation (Log Kow < 4).

white mineral oil (petroleum) (8042-47-5)

BCF - Other aquatic organisms [1] 1216 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)

Partition coefficient n-octanol/water (Log Pow) 5.18 (Experimental value)

Bioaccumulative potential Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

12.4. Mobility in soil

propane (74-98-6)

Surface tension No data available in the literature

Ecology - soil Not applicable (gas).

n-pentane (109-66-0)

Surface tension 15.49 mN/m (25 °C, 100 %)

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-pentane (109-66-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.9 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil.
dipropylene glycol monomethyl ether (34590-94-8)	
Surface tension	68.7 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. Not toxic to plants.
white mineral oil (petroleum) (8042-47-5)	
Surface tension	No data available in the literature, Data waiving
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.64 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Effect on global warming : No known effects from this product.





SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
1950	UN1950	1950	1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

DOT

UN-No. (DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

IMDG

Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

PCA Excepted quantities (IATA)	: E0
--------------------------------	------

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

n-pentane (109-66-0)

Listed on the Canadian DSL (Domestic Substances List)

naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on the Canadian DSL (Domestic Substances List)

dipropylene glycol monomethyl ether (34590-94-8)

Listed on the Canadian DSL (Domestic Substances List)

white mineral oil (petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

propane (74-98-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-pentane (109-66-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

dipropylene glycol monomethyl ether (34590-94-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

white mineral oil (petroleum) (8042-47-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
propane(74-98-6)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
n-pentane(109-66-0)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
dipropylene glycol monomethyl ether(34590-94-8)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness

Safety Data Sheet (SDS), USA

JAX America's Finest Penetrating Oil (Aerosol)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information and recommendations contained herein are, to the best of JAX INC.'s knowledge and belief, accurate and reliable as of the date issued. JAX INC. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC. shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC.'s interpretation of the available data.