

SAFETY DATA SHEET

JAX TEF-STEF (AEROSOL)

Infosafe No.: LQ3VR
ISSUED Date : 13/11/2019
ISSUED by: Industrial Lubricants & Services
Ltd

1. IDENTIFICATION

GHS Product Identifier

JAX TEF-STEF (AEROSOL)

Company Name

Industrial Lubricants & Services Ltd

Address

PO Box 259 347, Botany, Manukau 2163
Auckland, NEW ZEALAND

Telephone/Fax Number

Tel: 0800 10 40 11

Fax: 0800 10 40 15

Emergency phone number

0800 10 40 17

E-mail Address

orders@industlubes.co.nz

Recommended use of the chemical and restrictions on use

Lubricant where there may be incidental food contact.

Uses advised against: Not intended for direct food contact.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

2.1.2A (1 Danger) - Flammable aerosols (1)

6.3A Substance that is irritating to the skin

6.4A Substance that is irritating to the eyes

6.9 Narcotic

9.1B Substance that is ecotoxic in the aquatic environment

Signal Word (s)

DANGER

Hazard Statement (s)

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Flame, Exclamation mark, Environment



Precautionary statement – Prevention

- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash contaminated skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

- P101 If medical advice is needed, have product container or label at hand.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P362 Take off contaminated clothing and wash before reuse.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P391 Collect spillage.

Precautionary statement – Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

Other Information

Note: Pressurised container may burst if heated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
2-Methylpentane	107-83-5	25-50 %
Propane	74-98-6	10-25 %
Butane	106-97-8	10-25 %
2-Propanol	67-63-0	10-25 %
Ingredients determined not to be hazardous		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Unlikely due to form of product. If ingestion occurs, do not induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, alcohol foam and carbon dioxide.

Unsuitable Extinguishing Media

Do not use direct stream of water.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including formaldehyde, hydrogen fluoride, carbonyl fluoride, other fluorinated gases, carbon monoxide and carbon dioxide.

Specific Hazards Arising From The Chemical

Contents under pressure - cans can explode in a fire. This product is flammable. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

2YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Extinguish or remove all sources of ignition and stop leak if safe to do so. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. Place inert, Non-combustible absorbent material onto spillage. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

FLAMMABLE. VAPOUR OR GAS REDUCES OXYGEN FOR BREATHING. IN CONFINED SPACES MAY CAUSE ASPHYXIATION. Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Do not expose can to temperatures exceeding 50°C. Protect containers against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS 2278.1 Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive.

Storage Temperatures

Do not store above 49°C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

2-Propanol

TWA: 400 ppm, 983 mg/m³

STEL: 500 ppm, 1230 mg/m³

Butane

TWA: 800 ppm

TWA: 1900 mg/m³

Propane

NOTE: Asphyxiant

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Source: Workplace Exposure Standards and Biological Exposure Indices.

Biological Limit Values

Name: 2-Propanol

Determinant: Acetone in urine

Value: 40 mg/L

Sampling time: End of shift at end of workweek

Source: American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements. Refer to AS 2865 Australian Standard Safe working in a confined space, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as lined non-permeable rubber. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Other Information

Propane and Butane are asphyxiant gases which when present in an atmosphere in high concentration, lead to reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Aerosol - Liquid	Appearance	Colorless liquid with white powder (Liquid, powder and compressed gas in aerosol can)
Colour	Colourless	Odour	Fruity odour
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	Not available	Solubility in Water	Not available
Specific Gravity	0.68 (typical)	pH	Not available
Vapour Pressure	Not available	Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n-octanol/water	Not available
Flash Point	Not available	Flammability	Extremely flammable aerosol
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available		

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling.

Reactivity and Stability

Reacts with incompatible materials.

Conditions to Avoid

Avoid heat, sparks, open flames, welding arcs, direct sunlight or other high temperature sources.

Incompatible materials

Oxygen, strong oxidizers, selected amines, strong acids, strong bases, acetaldehyde, chlorine, ethylene oxide, fluorine, chlorine trifluoride, isocyanates. May be corrosive to lead and aluminum. Incompatible with finely divided metal powders.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: formaldehyde, hydrogen fluoride, carbonyl fluoride, other fluorinated gases, carbon monoxide and carbon dioxide.

Possibility of hazardous reactions

Hazardous reactions are not expected to occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material. The available toxicity data for ingredients given below.

Acute Toxicity - Oral

2-Propanol

LD50(rat): 5045 mg/kg

Acute Toxicity - Inhalation

2-Propanol

LC50(rat): 30 mg/l/4h

Butane

LC50(rat): 658 mg/l/4h

Ingestion

Unlikely due to form of product. If ingestion occurs, may cause lung damage if swallowed. Subsequent to ingestion or vomiting, small amounts of liquid aspirated into the respiratory system may cause severe pulmonary injury that may lead to death. May also cause irritation to the gastrointestinal system. Symptoms may include nausea, vomiting, diarrhoea and abdominal pain.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Propane and Butane are asphyxiant gases which when present in an atmosphere in high concentration, leads to reduction of oxygen concentration by displacement or dilution. Symptoms include decreased visual acuity, decreased coordination and judgment, headache, dizziness, confusion, drowsiness, fatigue, shortness of breath, muscular weakness, convulsions, unconsciousness, coma and eventually death.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

2-Propanol is listed as a Group {UD002}: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

Other Information

This material contains asphyxiant gas, which when present in an atmosphere in high concentrations, lead to a reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained. The minimum oxygen content in air should be 19.5 per cent by volume under normal atmospheric pressure. Unconsciousness and death can rapidly ensue in an environment, which is deficient in oxygen.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a flammable substance contained in a pressurised container .

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

Do not pierce, burn, cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. TRANSPORT INFORMATION

Transport Information

Road and Rail Transport:

This material is classified as Dangerous Goods Division 2.1 Flammable Gases

Class 1: Explosives

Division 2.3: Toxic gases

Class 3: Flammable liquids

Division 4.2: Spontaneously combustible substances

Division 4.3: Dangerous when wet substances

Division 5.1: Oxidising substances

Division 5.2: Organic peroxides

Class 7: Radioactive materials unless specifically exempted

Must not be loaded in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:

Division 4.1: Flammable Solids

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Proper Shipping Name: AEROSOLS (2-Methylpentane(MARINE POLLUTANT))

UN-No: 1950

Division: 2.1

EmS: F-D,S-U

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Proper Shipping Name: Aerosols,flammable

UN-No: 1950

Division: 2.1

Label: Flammable gas

Packaging Instructions (cargo only): 203

Packaging Instructions (passenger & cargo): 203

Special Provisions: A145, A167, A802

U.N. Number

1950

UN proper shipping name

AEROSOLS

Transport hazard class(es)

2.1

Hazchem Code

2YE

IERG Number

49

IMDG Marine pollutant

Yes

Transport in Bulk

Not available

Special Precautions for User

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Group Standard: Aerosols (Flammable) Group Standard 2006.

HSNO Approval Number

HSR002515

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Reviewed: November 2019

Supersedes: October 2014

References

Workplace Exposure Standards and Biological Exposure Indices.

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.