

# SAFETY DATA SHEET

**JAX FGH-AW ISO 32, 46, 68, 100**

Infosafe No.: LQ452  
ISSUED Date : 18/12/2019  
ISSUED by: Industrial Lubricants & Services  
Ltd

## 1. IDENTIFICATION

### GHS Product Identifier

JAX FGH-AW ISO 32, 46, 68, 100

### Company Name

Industrial Lubricants & Services Ltd

### Address

PO Box 259 347, Botany, Manukau 2163  
Auckland, NEW ZEALAND

### Telephone/Fax Number

Tel: 0800 10 40 11

Fax: 0800 10 40 15

### Emergency phone number

0800 10 40 17

### E-mail Address

orders@industlubes.co.nz

### Recommended use of the chemical and restrictions on use

Lubricant.

## 2. HAZARD IDENTIFICATION

### GHS classification of the substance/mixture

Not classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.  
Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Ingredients

Name	CAS	Proportion
White Mineral Oil (Petroleum)	8042-47-5	50-100 %
Ingredients determined not to be hazardous		Balance

## 4. FIRST-AID MEASURES

### Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

### Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.

### **Skin**

Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

### **Eye contact**

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

### **First Aid Facilities**

Eyewash and normal washroom facilities.

### **Advice to Doctor**

Treat symptomatically.

### **Other Information**

For advice in an emergency, contact a Poisons Information Centre contact or a doctor at once. (0800 764 766)

---

## **5. FIRE-FIGHTING MEASURES**

### **Suitable Extinguishing Media**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

### **Unsuitable Extinguishing Media**

Do not use water jet.

### **Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

### **Specific Hazards Arising From The Chemical**

This product will burn if exposed to fire.

### **Decomposition Temperature**

Not available

### **Precautions in connection with Fire**

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

---

## **6. ACCIDENTAL RELEASE MEASURES**

### **Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations.

If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

---

## **7. HANDLING AND STORAGE**

### **Precautions for Safe Handling**

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

### **Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well-ventilated area away from sources of ignition, foodstuffs, clothing and incompatible materials such as oxidising agents. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and

handling of flammable and combustible liquids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Occupational exposure limit values

No exposure standards have been established for this material, however, the TWA exposure standards for oil mist (mineral) is 5 mg/m<sup>3</sup>, STEL: 10 mg/m<sup>3</sup>. As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Source: Workplace Exposure Standards and Biological Exposure Indices.

### Biological Limit Values

No biological limits allocated

### Appropriate Engineering Controls

Provide sufficient ventilation to keep airborne levels below the exposure limits or as low as possible. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required.

Refer to relevant regulations for further information concerning ventilation requirements.

### Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

### Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

### Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

### Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Liquid	Appearance	Liquid
Colour	Water white.	Odour	Nearly odourless
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	Not available	Solubility in Water	Not available
Specific Gravity	Not available	pH	Not available
Vapour Pressure	Not available	Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n-octanol/water	Not available
Density	0.86 g/cm <sup>3</sup> at 20°C	Flash Point	204°C (ASTM D 92)
Flammability	Not flammable	Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available	Flammable Limits - Upper	Not available
Explosion Properties	Product does not present an explosion hazard.	Oxidising Properties	Not available

## 10. STABILITY AND REACTIVITY

### Reactivity

Reacts with incompatible materials.

### Chemical Stability

Stable under normal conditions of storage and handling.

### Conditions to Avoid

Heat, direct sunlight, flames and other sources of ignition. Direct sunlight.

### Incompatible materials

Avoid strong oxidants, strong alkalis and strong acids.

### Hazardous Decomposition Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

### Hazardous Polymerization

Not available

## 11. TOXICOLOGICAL INFORMATION

### Toxicology Information

No toxicity data available for this material.

### Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

### Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

### Skin

May be irritating to skin. The symptoms may include redness, itching and swelling.

### Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

**Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

**Skin Sensitisation**

Not expected to be a skin sensitiser.

**Germ cell mutagenicity**

Not considered to be a mutagenic hazard.

**Carcinogenicity**

Not considered to be a carcinogenic hazard.

**Reproductive Toxicity**

Not considered to be toxic to reproduction.

**STOT-single exposure**

Not expected to cause toxicity to a specific target organ.

**STOT-repeated exposure**

Not expected to cause toxicity to a specific target organ.

**Aspiration Hazard**

Not expected to be an aspiration hazard.

## 12. ECOLOGICAL INFORMATION

---

**Ecotoxicity**

No ecological data available for this material.

**Persistence and degradability**

Not available

**Mobility**

Not available

**Bioaccumulative Potential**

Not available

**Other Adverse Effects**

Not available

**Environmental Protection**

Prevent this material entering waterways, drains and sewers.

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal considerations**

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

**Product Disposal:**

This product can be disposed through a licensed commercial waste collection service. This product is non-hazardous and therefore the New Zealand HSNO regulations regarding disposal do not apply, however other regulations may apply.

This product is a non-hazardous, combustible substance; It should be recycled whenever possible or sent to an approved high temperature incineration plant for disposal.

**Container Disposal:**

The product is non-hazardous, therefore, the packaging may be re-used or recycled if it has been treated to remove any residual contents of the substance. Any wash-off water from the container cleaning process should be sent to a suitable waste water treatment plant before discharge into the environment.

In New Zealand, the packaging (that may or may not contain any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

## 14. TRANSPORT INFORMATION

---

**Transport Information**

Road and Rail Transport:

Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2012 Transport of Dangerous Goods on Land.

Marine Transport (IMO/IMDG):

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport (ICAO/IATA):

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

**U.N. Number**

None Allocated

**UN proper shipping name**

None Allocated

**Transport hazard class(es)**

None Allocated

**IMDG Marine pollutant**

No

**Transport in Bulk**

Not available

**Special Precautions for User**

Not available

---

**15. REGULATORY INFORMATION****Regulatory information**

Not classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

---

**16. OTHER INFORMATION****Date of preparation or last revision of SDS**

SDS Reviewed: December 2019 Supersedes: January 2015

**References**

- Workplace Exposure Standards and Biological Exposure Indices.
- Transport of Dangerous goods on land NZS 5433.
- Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).
- Assigning a hazardous substance to a group standard.
- Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

**END OF SDS**

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.