



MSDS SUPPLEMENT TO GHS REGULATIONS

To comply with the Hazardous Substance and New Organisms Act, this coversheet offers New Zealand specific information. This page “0”, is to be considered part of the MSDS.

PRODUCT NAME & COMPANY IDENTIFICATION

Product Name	Date of Issue
FLOW-GUARD SYN GEAR OIL - ISO 460	2/03/2023

Company Name	Industrial Lubricants & Services Ltd 1/15 Accent Drive East Tamaki Auckland 2013
--------------	---

Emergency Contact	<i><u>National Poisons Centre - NZ</u></i> <i>0800 764 766 or Chemcall 0800 243 622</i>
-------------------	--

Hazard Identification

As per Hazardous Substances (Hazard Classification) Notice 2020, this material is classified:

GHS 7 / REACH

Reproductive toxicity Category 2

H361 - Suspected of damaging fertility or the unborn child

According to criteria in Transport of Dangerous Goods on Land NZS 5433:2020 this product is not regulated or considered Dangerous Goods for Transport

Other Identification

HSN (Tariff Code)	2710.12.59 19B
Shelf Life	5 Years



JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 3/2/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : JAX Flow-Guard Synthetic Fluid ISO 460
Product code : FGS460

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricant where there may be incidental food contact

1.3. Supplier

JAX INC.
W134N5373 Campbell Drive
Menomonee Falls, WI 53051
T (262) 781-8850
info@jax.com

1.4. Emergency telephone number

Emergency number : Infotrac : North America 1-800-535-5053 | International 1-352-323-3500

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Reproductive toxicity Category 2 H361 Suspected of damaging fertility or the unborn child
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H361 - Suspected of damaging fertility or the unborn child
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

98.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

98.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

98.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	CAS-No.: 68411-46-1	<1.0

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

JAX Flow-Guard Synthetic Fluid ISO 460

No additional information available

benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 453 °F (234°C) min., ASTM D 92
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.83 – 0.87 (typical)
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

JAX Flow-Guard Synthetic Fluid ISO 460

Unknown acute toxicity (GHS US)	98.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 98.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 98.35% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
---------------------------------	--

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Skin)

Skin corrosion/irritation : Not classified

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

pH	5.1 – 6.2 (1 %, 20 - 25 °C)
----	-----------------------------

Serious eye damage/irritation : Not classified

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

pH	5.1 – 6.2 (1 %, 20 - 25 °C)
----	-----------------------------

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.

JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

NOAEL (oral,rat,90 days)	25 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Viscosity, kinematic	353 mm ² /s (40 °C, OECD 114: Viscosity of Liquids)
----------------------	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	51 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

12.3. Bioaccumulative potential

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

BCF - Fish [1]	1730 (42 day(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across, GLP)
Partition coefficient n-octanol/water (Log Pow)	6.66 (Experimental value, OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

12.4. Mobility in soil

benzamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Mobility in soil	60460 Source: EPISUITE
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.754 – 8.947 (log Koc, SRC PCKOCWIN v2.0, QSAR)

JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Ecology - soil

Adsorbs into the soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

JAX Flow-Guard Synthetic Fluid ISO 460

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H361	Suspected of damaging fertility or the unborn child
------	---

Safety Data Sheet (SDS), USA

The information and recommendations contained herein are, to the best of JAX INC.'s knowledge and belief, accurate and reliable as of the date issued. JAX INC. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and JAX INC. shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with JAX INC.'s interpretation of the available data.