## **TECHNICAL DATA SHEET**



Whitmore's expertise in lubricating open gear lubrication has been distilled into Earthkeeper<sup>®</sup> OGL, a highly effective lubricant for use on open gears that are found on Draglines, Shovels, Kilns and Ball Mills.

Earthkeeper<sup>®</sup> OGL is formulated using a high concentration of solid lubricants in combination with extreme pressure additives. It forms a robust film that protects from scuffing and pitting under the most punishing conditions.

Earthkeeper  $^{\odot}$  OGL has been tested by an independent lab and found to contain 73% renewable ("biobased") materials.

## **BENEFITS:**

- BIODEGRADABLE it will pass the OECD 301B test for "ready biodegradability".
- WEAR PROTECTION forms a tenacious and highly protective lubricating film.
- PROVEN TECHNOLOGY uses a tried and proven additive system in combination with biodegradable oils.
- OEM SPEC CONFORMANCE meets the requirements of CAT/Bucyrus SD4713 at ambient temperatures from -4°F to +104°F (-20°C to +40°C). Grades that are suitable for use on the hoist gear of model 495 shovels can be formulated on request.

## **APPLICATIONS:**

Use Earthkeeper<sup>®</sup> OGL on open applications of Draglines and Shovels (open gears, house rollers, etc.) Also suitable for the open gears of Ball Mills and Kilns.

| ASTM #             |   | TYPICAL CHARACTERISTICS |
|--------------------|---|-------------------------|
|                    | NLGI Grade  | 0                       |
| D-217              | Cone Penetration (Worked)   | 355-385                 |
| D-2265             | Dropping Point, °F (°C)   | >600 (316)              |
| D-445              | Kinematic Viscosity (Base oil)<br>cSt @ 40°C<br>cSt @ 100°C               | 1,902<br>83.10          |
| Gardner<br>Method  | Density, lb/gal @ 60°F (15.5°C)<br>Specific Gravity, g/cc @ 60°F (15.5°C) | 9.15<br>1.098           |
| D-2596             | Four Ball EP<br>Weld Point, kg  | 800                     |
| D-2266             | Four Ball Wear<br>Scar Width, mm  | 0.70                    |
| D-1743             | Rust Test   | Pass                    |
| D-4048<br>Modified | Copper Strip Corrosion for Greases<br>212°F (100°C) @ 3 hrs               | 1B                      |
|                    | Thickener Type  | Inorganic               |
| OEM<br>Standard    | Low Temperature Pumpability<br>Lincoln Ventmeter @ 450 psi, °F (°C)       | 24 (-4)                 |

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

| Shuttle Tanks Nonreturnable Drums Pails |
|---|
|---|

For warranty information, scan the QR code. You can also email us at <u>sales@whitmores.com</u>

Or write to the Sales Department at the address below.



930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318 An ISO 9001 and ISO 14001 registered company • <u>www.whitmores.com</u>