



## Technical Data sheet

# AIR SENTRY Z-SERIES



Z-Series breathers are designed for applications where space is limited or air flow requirements are lower than 5 cfm. The Z-Series is typically used on gearboxes and low fluid volume applications where mounting space is limited or where a larger breather will not fit without remote mounting.

Limited Space Applications - Gearboxes • Drums • Totes • Small Oil Containers

### SPECIFICATIONS

Model	Height Inches (cm)	Diameter	Mounting Connector	Silica Gel lbs (kg)	Max Absorbtion Capacity FL Ounces (ml)	Max Air Flow	Max Reservoir Fluid Flow	Type of Medium
Z-131	2 (5.1)	2 (5.1)	1/2" FNPT	0.08 (0.04)	0.49 (14)	5 cfm	37 gpm	100% Silica Gel
Z-132	2 (5.1)	3.25 (8.3)	1/2" FNPT	0.1 (0.05)	0.92 (27)	5 cfm	37 gpm	100% Silica Gel
Z-133	3.25 (8.3)	2 (5.1)	1/2" FNPT	0.3 (0.1)	1.84 (54)	5 cfm	37 gpm	100% Silica Gel
Z-134	3.25 (8.3)	3.25 (8.3)	1/2" FNPT	0.5 (0.2)	3.06 (90)	5 cfm	37 gpm	100% Silica Gel
Z-135	3.25 (8.3)	5.5 (14.0)	1/2" FNPT	0.8 (0.4)	4.91 (145)	5 cfm	37 gpm	100% Silica Gel