



Castrol Transmax Z

Automatic Transmission Fluid

Description

Castrol Transmax Z, formulated with Smooth Drive Technology™, is a full synthetic automatic transmission fluid recommended for use in automatic and semi-automatic transmissions in cars, buses and coaches. It can solve shiftability problems in automatic transmissions, enabling longer transmission life. It is recommended for fleets employing a mixture of Voith, Renk, ZF, Allison and MB transmissions alongside the Leyland Pneumocyclic and Hydracyclic units. Approved for extended oil drain (120,000 km) in ZF Ecomat and EcoLife, Mercedes-Benz and Voith automatic transmissions.

Castrol Transmax Z, formulated with Smooth Drive Technology™, delivers enhanced protection and gives drivers a smoother drive for longer.

Advantages

- Enhanced friction durability for smooth transmission performance
- Enhanced wear protection provides longer component life, extended drain capability and reduced operating costs
- Excellent thermal and oxidative stability to effectively resist fluid degradation and maintain operational efficiency for longer
- Enhanced protection against deposits extends transmission life
- Temperature reduction in severe service improves transmission and oil service life and helps reduce fuel consumption and emissions
- Outstanding cold flow properties protect transmission components especially at start-up
- A problem-solver for gear shiftability issues with over 15 years of trouble-free field performance

Typical Characteristics

Name	Method	Units	Transmax Z
Density @ 15°C, Relative	ASTM D4052	g/ml	0.836
Viscosity, Kinematic @ 40°C	ASTM D445	mm ² /s	38
Viscosity, Kinematic @ 100°C	ASTM D445	mm ² /s	7.5
Viscosity Index	ASTM D2270	None	170
Viscosity, Brookfield @ -40°C	ASTM D2983	mPa.s (cP)	8400
Pour Point	ASTM D97	°C	-66
Flash Point, COC	ASTM D92	°C	228

Product Performance Claims

MAN 339 Typ Z3, MAN 339 Typ Z12, MAN 339 Typ V2,

ZF TE-ML 04D,11B,14C,16M,16S, 20C, 25C

VW 501 60

MB-Approval 236.81

Voith H55.6336.xx

JASO 1A

Recommended for use where:

- Toyota T, T II, T III, T IV, WS
- Nissan Matic D, J, S
- Mitsubishi SP II, IIM, III, PA, J3, SP IV
- Mazda ATF M-III, M-V, JWS 3317, FZ
- Subaru F6, Red 1
- Daihatsu AMMIX ATF D-III Multi, D3-SP
- Suzuki AT Oil 5D06, 2384K, JWS 3314, JWS 3317
- Hyundai/Kia SP III, SP IV
- Aisin Transmissions requiring JWS 3309
- Honda/Acura DW 1/Z 1
- Isuzu (where Toyota T-IV is required)

is required.

Suitable for use in BMW, VW, Audi and Jaguar 5 speed automatic transmission and MB 4 and 5 speed automatic transmissions.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax Z

15 Dec 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz