



Castrol GTX Professional 10W-30

50% better protection against sludge

Description

Castrol GTX Professional is one of the world's most trusted motor oils. It's more than just oil. It's liquid engineering that protects against problems, like sludge, that your engine faces every day.

Severe driving conditions such as every day stop-and-go/stop-start traffic, harsh weather conditions and extended drain intervals, can all cause the build-up of a thick, tar-like substance called sludge.

You can't see this sludge build-up but it can damage your engine's performance and cause premature engine failure.

Protect your car from harmful sludge build-up with Castrol GTX Professional.

Application

Castrol GTX Professional 10W-30 with SYNTHETIC TECHNOLOGY is suitable for use in automotive petrol and diesel engines where the manufacturer recommends an ACEA A3/B3, API SN/CF or earlier specification 10W-30 lubricant.

Advantages

Castrol GTX Professional 10W-30 with SYNTHETIC TECHNOLOGY:

- Contains anti-sludge formula that provides 50% better sludge protection compared to tough industry standards*
- Provides superior protection against viscosity and thermal breakdown
- Features Anti-wear additives that extend the life of your engine
- Is micro filtered using the same filtration process that motor manufacturers demand and use when they fill the engine with oil for the very first time, it's your guarantee of Professional quality.

* As tested against the API /ACEA Sequence VG engine test

Typical Characteristics

Name	Method	Units	Castrol GTX Professional 10W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.8682
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	12.4
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6700
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	85
Viscosity Index	ASTM D2270	None	143
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	202
Ash, Sulphated	ASTM D874	% wt	0.9

Product Performance Claims

ACEA A3/B3
API SN/CF

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Professional 10W-30

28 Aug 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz