# PRODUCT DATA

# **Castrol Garden 2T**

## PRODUCT DESCRIPTION

**Castrol Garden 2T** is an advanced high quality 2-stroke engine oil specially designed to give good anti-wear and antiseizure properties for use in lawn mowers, chain saws and other garden machinery.

## PRODUCT APPLICATION

**Castrol Garden 2T** is suitable for all 2T garden equipment and for use in pre-mix and oil injection systems with unleaded petrol. Depending on the engine manufacturers recommendation, **Castrol Garden 2T** can be used up to an oil/fuel ratio of 50:1.

**Note:** Some engine manufacturers recommend a different oil/fuel ratio when using a genuine two stroke oil.

**Castrol Garden 2T** is not recommended for water-cooled two-stroke marine outboards. For these applications, **Castrol Super Outboard Plus** is recommended.

#### PRODUCT FEATURES & BENEFITS

- Protection from build up of carbon deposits
- Fully miscible with all petrol fuel and dyed dark blue for ease of identification
- Good anti-wear and anti-seizure properties
- Prevention from spark plug fouling

#### TYPICAL CHARACTERISTICS

SAE Viscosity Grade	Density kg/ @ 15°C	Sulphated Ash %	Total Base Number (TBN) mg KOH/g	Colour
30	0.885	0.12	3.58	Dark Blue

#### **STORAGE**

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



# **HEALTH, SAFETY & ENVIRONMENT**

**Castrol Garden 2T** is considered non-hazardous in accordance with the HSNO Act. However, in line with safe handling practices, it is recommended that the handling instructions outlined in the Castrol Material Safety Data sheet be followed.

**Spillage** 

Small: Soak up using an inert mineral adsorbent such as Castrol MOP S

and dispose of in the appropriate manner.

Large: Corrective action usually dictated by individual company safety

procedures. Immediate containment and subsequent removal is

essential.

**Disposal:** Oily materials must not be allowed to enter groundwater,

watercourses, sewerage or drainage systems. Refer to local Waste

Disposal Authority for legal requirements.

**Product Removal** 

Bare Metal Surfaces: Remove with Castrol solvent cleaners or water based degreasers.

**Hand Cleaning:** Use any of the Castrol range of hand cleaners, e.g. CareClean Plus.

Other Surfaces: Contact the Castrol Technical Advice Line on 0800 10 40 60.

25/02/13

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products,

For more information contact: Castrol NZ (A Business Division of BP Oil New Zealand Limited)
Technical Advice Line: 0800 10 40 60

