



## Castrol Transmax DEXRON®-VI MERCON® LV

Automatic Transmission Fluid

### Description

Castrol Transmax DEXRON®-VI MERCON® LV, formulated with Smooth Drive Technology™, is designed for modern automatic transmissions. Its superior technology enables longer transmission life. Transmax DEXRON®- VI MERCON® LV is approved and licenced by GM and Ford for use in vehicles requiring their latest ATF specifications and also exceeds the requirements of the JASO-1A performance standard limits for use in most Asian automatic transmissions. Transmax DEXRON®-VI MERCON® LV, formulated with Smooth Drive Technology™, delivers enhanced protection and gives drivers a smoother drive for longer.

### Advantages

- OEM approved and licensed by Ford (MERCON® LV) and GM (DEXRON®-VI)
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Recommended for use in most automatic transmissions

### Typical Characteristics

Name	Method	Units	Transmax DEXRON®-VI MERCON® LV
Colour	Visual	-	Red
Density @ 15°C, Relative	ASTM D4052	g/ml	0.841
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	30
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	5.9
Viscosity Index	ASTM D2270	None	161
Viscosity, Brookfield @ -40°C	ASTM D2983	mPa.s (cP)	10000
Pour Point	ASTM D97	°C	-54

## Product Performance Claims

MERCON® LV

DEXRON® VI

Suitable for use where JASO 1A(03)

JASO 1A LV(13) is required including:

Toyota T III, T IV, WS

Mitsubishi SP II, IIM, III, IV, PA, J3

Mazda ATF M-III, M-V, FZ

Honda/Acura DW 1/Z 1

Nissan Matic D, J, S

JWS 3314/3317/ 3309, Suzuki AT Oil 5D06, 2384K

Isuzu

Subaru F6, Red 1

Daihatsu AMMIX ATF D-III Multi, D3-SP

Hyundai/Kia SP III, SP IV

Also suitable for use in 6-speed automatics from Audi, BMW, Mini-Cooper, Jaguar, Peugeot/Citroen, Saab, Volvo, VW, Porsche, and all vehicles where Dexron III or Mercon SP is required.

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax DEXRON®-VI MERCON® LV

16 Apr 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)  
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)  
[www.castrol.co.nz](http://www.castrol.co.nz) [www.msds.castrol.co.nz](http://www.msds.castrol.co.nz)