

EDGE 0W-40 A3/B4

Unlock the very edge of performance.

Description

For over 15 years, Castrol EDGE has been helping drivers unlock the very edge of performance, and the current generation of Castrol EDGE engine oils are no different.

Formulated with advanced full synthetic technology, Castrol EDGE is tested to the highest standards to deliver the high-performance levels expected by drivers and by world-leading car manufacturers in their latest engine technology.

The ultimate test of performance, on the track Castrol EDGE products are pushed to the limit by some of the best in world motorsport.

Application

Castrol EDGE 0W-40 A3/B4 is suitable for use in automotive petrol and diesel vehicles where the manufacturer recommends an ACEA A3/B4, API SP or earlier specification 0W-40 lubricant.

Castrol EDGE 0W-40 A3/B4 is approved for use by leading car manufacturers.

Please refer to the product performance section and your owners handbook

Advantages

Castrol EDGE 0W-40 A3/B4:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure
- Delivers high levels of fuel efficiency and low temperature performance

Typical Characteristics

Name	Method	Units	Castrol EDGE 0W-40 A3/B4
Density @ 15C, Relative	ASTM D4052	g/ml	0.844
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.3
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	76
Viscosity Index	ASTM D2270	None	180
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5980
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% wt	1.2

Product Performance Claims

ACEA A3/B4

API SP

BMW Longlife-01

MB-Approval 229.5

Porsche A40

Renault RN 0700 / RN0710

VW 502 00/ 505 00

Meets Ford WSS-M2C937-A

Warranted by Castrol to be completely suitable for use in vehicles where the following specifications apply: MB 229.3

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

EDGE 0W-40 A3/B4

12 Mar 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited

Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)

www.castrol.co.nz www.msds.castrol.co.nz