



## Techniclean AS 62

Hydrocarbon solvent cleaner

### Description

Castrol Techniclean™ AS 62 is a fast drying, low aromatic solvent cleaner. It has excellent solvency power and is compatible with all metal substrates and most non-metal substrates. Techniclean AS 62 has been developed specifically as an alternative to chlorinated solvent cleaners and traditional high aromatic-containing hydrocarbon solvent cleaners.

### Application

•**Soak Tank** Components should be fully immersed in neat product. Contact time depends on soil severity. •**Ultrasonic Tank** Components should be fully immersed in neat product. •**Wipe Method** Product should be applied neat via hand held spray or brush and the surface is then wiped to a clean, dry finish.

### Advantages

- Excellent solvency power against animal, vegetable and mineral fats and oils and very low surface tension, allowing the fluid to penetrate into difficult to reach areas – improves parts cleanliness and reduces re-work
- Fast drying, residue-free finish – increases productivity and minimises scrap-rate
- Based on a solvent with low aromatic content – improves environment for workforce
- No waste water is produced and solvent can be recycled by distillation – highly effective and yet economical

### Typical Characteristics

Name	Method	Units	
Appearance	Visual	-	clear, colourless liquid
Density @ 15°C	ISO 12185	kg/m <sup>3</sup>	792
Initial boiling point	ISO 3405	°C	> 180
Flash Point PMCC	ISO 22719	°C	> 62

## User Advice

- May swell some rubber and plastics during long-term contact.
- Should not be used for cleaning live electrical equipment.

Techniclean AS 62

15 Jun 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited  
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)  
[www.castrol.co.nz](http://www.castrol.co.nz) [www.msds.castrol.co.nz](http://www.msds.castrol.co.nz)