



## Spheerol™ Ultratak 2

Multipurpose lithium complex grease

### Description

Castrol Spheerol™ Ultratak 2 is a multipurpose lithium complex grease which has special properties in wet environments. A unique synthetic polymer incorporated into Spheerol Ultratak grease gives it the ability to build adhesion and tackiness in the presence of water. This ability can dramatically decrease the water "washout" associated with standard greases.

In addition Spheerol Ultratak 2 grease also has excellent resistance to corrosion, even in salt water conditions.

Spheerol Ultratak 2 grease has outstanding load carrying and antiwear properties which will provide protection to equipment operating under a wide range of conditions.

### Application

Spheerol Ultratak 2 is suitable for many applications such as plain bearings, ball and roller bearings, ball joints and bucket pins. It outperforms standard greases in areas where excellent resistance to corrosion and water washout are required.

### Advantages

- Unique synthetic polymer.
  - Builds adhesion and tackiness in wet conditions – resists water washout
- Powerful corrosion inhibitor.
  - Protects against corrosion in wet environments – reduces equipment damage due to rust
- Extreme pressure and antiwear additives.
  - Provides excellent protection against wear, even in heavy load applications – optimum equipment protection

## Typical Characteristics

Name	Method	Units	Typical Results
Viscosity, Target Base Oil 40C	Calculated	mm <sup>2</sup> /s	500
Penetration, worked 60 Cycles	ASTM D217	1/10 mm	290 - 320
Colour	Visual	-	Red
NLGI Class	Grade	-	2
Dropping Point, Grease	ASTM D2265	°C	>200
Weld Point @ 800 kg (sec)	IP 239	Kg	>10
Penetration Difference between Worked/Unworked	ASTM D217	1/10 mm	+/- 20

Subject to usual manufacturing tolerances

Spheerol™ Ultratak 2

05 Mar 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)

Technical Advice Line: 0800 10 40 60 / Customer Service: 0800 CASTROL (227 876)

<http://msdspd.castrol.com>