



Castrol EDGE 0W-30 C2

Fluid TITANIUM - Stronger Under Pressure

Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE with patented Fluid TITANIUM transforms its physical structure to be stronger under pressure to keep metal apart and reduces friction for maximum engine performance when you need it most.

Castrol EDGE with Fluid TITANIUM: unlock the true performance of your engine.

Application

Castrol EDGE 0W-30 C2 is an advanced full synthetic engine oil suitable for use in automotive petrol and diesel engines where the manufacturer recommends an ACEA C2 0W-30 lubricant.

Castrol EDGE 0W-30 C2 is approved for use in vehicles that require Jaguar Land Rover engine oil specification STJLR.03.5007 0W-30 lubricant.

Advantages

Castrol EDGE 0W-30 C2 with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's modern vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE 0W-30 C2:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across all engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure
- Delivers high levels of fuel efficiency and low temperature performance

Typical Characteristics

| Name | Method | Units | Castrol EDGE 0W-30 C2 |
|---------------------------|------------|------------|-----------------------|
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.844 |
| Viscosity, Kinematic 100C | ASTM D445 | mm²/s | 9.8 |
| Viscosity, CCS -35C (0W) | ASTM D5293 | mPa.s (cP) | 5252 |
| Viscosity, Kinematic 40C | ASTM D445 | mm²/s | 52 |
| Viscosity Index | ASTM D2270 | None | 176 |
| Pour Point | ASTM D97 | °C | -48 |
| Flash Point, PMCC | ASTM D93 | °C | 205 |
| Ash, Sulphated | ASTM D874 | % wt | 0.79 |

Product Performance Claims

ACEA C2

Jaguar Land Rover engine oil specification STJLR.03.5007

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited

Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876) www.castrol.co.nz www.msds.castrol.co.nz