

Adblue

Diesel exhaust fluid

Description

Castrol Adblue is a high quality AUS/32 Diesel Exhaust Fluid conforming to the ISO 22241 specification

Conditions of Use

- Fill into the designated tank for DEF/AUS. Do not fill into diesel/ fuel tanks.
- Once opened, the container should be consumed in full to avoid contamination and negative impact on product quality.
- Avoid contamination with fuel or oil. Use a dedicated spout to pour Castrol Adblue into the tank.
- · Keep away from dust and dirt.

Typical Characteristics

| Name | Method | Units | Adblue |
|--------------------------|---------------------|--------------|-----------------|
| Urea Content | ISO 22241-2 (B & C) | % by w eight | 31.8 - 33.2 |
| Density @ 20C | Supplier | g/ml | 1.087 - 1.093 |
| Refractive Index at 20°C | Supplier | - | 1.3814 - 1.3843 |
| Biuret | ISO 22241-2 (E) | mg/kg | 0.3 max |
| Aldehyde content | ISO 22241-2 (F) | mg/kg | 5 max |
| Insoluble Matter | ISO 22241-2 (G) | mg/kg | 20 max |

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Adblue

21 Feb 2025

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www castrol com