



## Castrol Transmax CVT

CVT Fluid

### Description

Castrol Transmax CVT, formulated with Smooth Drive Technology™, is a full synthetic fluid for use in continuously variable transmissions (CVT) of most passenger cars. Its superior technology enables longer transmission life. It can be recommended for use in most passenger cars fitted with push belt or chain technologies. Castrol Transmax CVT, formulated with Smooth Drive Technology™, provides higher torque capacity and enhanced wear protection, extending the fluid performance and giving drivers a smoother drive for longer.

### Advantages

- Higher torque capacity
- Enhanced wear protection in the push belt–pulley interface
- Superior operational efficiency with reduced risk of belt-slippage
- Improved oxidative stability with excellent viscosity control

### Typical Characteristics

Name	Method	Units	Transmax CVT
Density @ 15C, Relative	ASTM D4052	g/ml	0.849
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	7.1
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	34
Viscosity Index	ASTM D2270	None	179
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	9200
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	214

## Product Performance Claims

Suitable for use where the following are called for: Toyota CVT Fluid TC, FE

Nissan CVT Fluid NS-1, NS-2, NS-3

MMC DIAQUEEN ATF SP-III, CVT Fluid J1, CVT Fluid J4, CVT Fluid J4+

Mazda CVTF 3320, Subaru i-CVT Fluid, i-CVT FG, Lineartronic II

Lineartronic High Torque Chain CVTF

Daihatsu AMMIX CVT Fluid DC, CVT Fluid DFE

Suzuki CVT Fluid 3320, Green 1, Green 2, CVTF TC, NS-2

Honda HCF-2 \*

Hyundai/Kia SP-III, SP-CVT 1

Chrysler NS-2, CVTF+4

Mini Cooper EZL799

Ford CVT23

MB 236.20

VW/Audi TL 52180 (G 052 180), TL 52516 (G 052 516)

Dex CVT

\*Transmax CVT is suitable for use in all of Honda CVTs except 2001-2007 Model Honda Fit/Jazz which are equipped with Starting Clutch.

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax CVT

30 Mar 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited

Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)

[www.castrol.co.nz](http://www.castrol.co.nz) [www.msds.castrol.co.nz](http://www.msds.castrol.co.nz)