

## Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

Automatic Transmission Fluid

### Description

Castrol Transmax ATF DEXRON®-VI MERCON® LV Multivehicle, formulated with Smooth Drive Technology™, is a Full Synthetic Technology formulation designed for modern automatic transmissions. Its superior technology enables longer transmission life. Transmax ATF DEXRON®-VI MERCON® LV Multivehicle is approved and licenced by GM and Ford for use in vehicles requiring their latest ATF specifications and also exceeds the requirements of the JASO-1A for use in most Asian automatic transmissions. Transmax ATF DEXRON®-VI MERCON® LV Multivehicle is also suitable for use in the majority of 6,7,8 and 9 speed automatics of European cars, meaning it is suitable for use in nearly all passenger car automatic transmissions. It delivers enhanced protection and a smoother drive for longer.

### Advantages

- OEM approved and licensed by Ford (MERCON® LV) and GM (DEXRON®-VI)
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Recommended for use in most automatic transmissions

### Typical Characteristics

Name	Method	Units	Transmax ATF Dexron-VI Mercon LV Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.841
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	6.0
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	30
Viscosity Index	ASTM D2270	None	161
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	10000
Pour Point	ASTM D97	°C	-54
Flash Point, COC	ASTM D92	°C	218

## Product Performance Claims

Ford MERCON® LV, GMDEXRON® -VI

Suitable for use where the following are called for: Aisin Warner AW-1, AW-2

AML Oil No. G 055005 A1 / A2 / A6

ATF M1375.4

D3M

MA-1

SP

Bently Oil No. PY112995PA

BMW Oil No. 8322 0142516, 83 22 2 3 55 599 (ATF6), 83 22 2 413 477 (ATF7), 83 22 2 289 720 (ATF3+), ETL 7045E, LA 2634, LT 71141

Chrysler Oil No. 68157995AA, ATF+4

Daihatsu AMMIX ATF D-III Multi D3-SP

Ford MERCON® ULV ATF MERCON SP, M2C924-A, M2C949-A

GM 1940767, GM DEXRON II, III, IIH

Honda ATF Type 3.1 : 08263-999--01HE (EU), Honda/Acura DW 1/Z 1

Hyundai/Kia SP III, SP IV, SP IV M, SP IV RR

Oil No. 040000C905G

Isuzu, Red 1

Jaguar Oil No. 02JDE 26444, Fluid 8432

JASO 1A(03)

JASO 1A LV(13)

JWS 3314, 3317, 3309, 3324

Land Rover Oil No. LR023288, TYK500050

MB 236.10, 236.12, 236.14, 236.15, 236.17

Maserati Oil No. 231603

Mazda ATF M-III, M-V, FZ

Mitsubishi SP II, IIM, III, IV, PA, J3

Nissan Matic D, J, S

Subaru F6, Red 1

Suzuki AT Oil 5D06, 2384K

Toyota T III, T IV, WS

Volvo 1161540

VW / Audi G 052 990, TL52990, VW / Audi G 055 540

TL 55540, VW / Audi G 060 162

TL 60162, ZF Lifeguardfluid 6, ZF Lifeguardfluid 8

the OFF ROAD application Volvo 97342 (AT 102) Porsche. 7 and 9 speed automatics from Mercedes Benz

and 8 and 9-speed automatics from Audi, BMW, Mini-Cooper

Jaguar, Peugeot/Citroen, Saab, Volvo, and VW

whose specification or part number is not specifically mentioned above.

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

15 Aug 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited

Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)

[www.castrol.co.nz](http://www.castrol.co.nz) [www.msds.castrol.co.nz](http://www.msds.castrol.co.nz)