



Transmax Power Steering Fluid

Automatic Transmission & Power Steering Fluid

Description

Castrol Transmax Power Steering Fluid may be used in power steering units of many types of vehicles where DEXRON®-IIIH, DEXRON®-IID, MERCON®, or JASO-1A type performance is required.

Advantages

- Efficient operation of power steering units in all conditions

Typical Characteristics

Name	Method	Units	Transmax Power Steering Fluid
Appearance	Visual	-	Clear & Bright
Colour	ASTM D1500	-	Red spectrum
Density @ 15°C, Relative	ASTM D4052	g/ml	0.851
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	7.4
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	35
Viscosity Index	ASTM D2270	None	185
Viscosity, Brookfield @ -40°C (75W)	ASTM D2983	mPa.s (cP)	16200
Pour Point	ASTM D97	°C	-51
Flash Point, PMCC	ASTM D93	°C	200

Product Performance Claims

JASO 1A 03

Meets - Ford MERCON®, GMDEXRON® -IIH

MeetsDEXRON® -IIH, MERCON®

Suitable for use where JASO 1A(03)

JASO 1A LV(13) is required including:

Toyota T III, T IV, WS,

Mitsubishi SP II, IIM, III, IV, PA, J3,

Mazda ATF M-III, M-V, FZ,

Honda/Acura DW 1/Z 1,

Nissan Matic D, J, S,

JWS 3314/3317/ 3309,

Suzuki AT Oil 5D06, 2384K,

Isuzu,

Subaru F6,

Red 1,

Daihatsu AMMIX ATF D-III Multi, D3-SP,

Hyundai/Kia SP III, SP IV,

Suitable for use as Power steering fluid

Transmax Power Steering Fluid

29 Mar 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited

Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)

www.castrol.co.nz www.msds.castrol.co.nz