

Castrol GTX Diesel 15W-40

CLEANER FOR LONGER. HELPS EXTEND ENGINE LIFE

Description

Castrol GTX is one of the world's most trusted engine oils.

The modern world creates difficult challenges for engines.

Poor fuel quality, heat and frequent short trips can all lead to sludge that potentially shortens engine life. Sludge is a sticky deposit that can block your engine's vital oilways and if untreated it can rob an engine of power and, ultimately, its life.

Castrol GTX with **3X CLEAN** formula works to **Catch, Control** and **Clean** dirt from engine oilways, keeping your engine cleaner for longer and helping to extend engine life.

Castrol GTX also protects against new sludge formation better than tough industry standards*.

Help extend the life of your engine with Castrol GTX.

Application

Castrol GTX Diesel 15W-40 is suitable for use in automotive petrol, LPG, CNG and diesel engines where the manufacturer recommends an ACEA A3/B4, API SP or earlier specification 15W-40 lubricant.

Advantages

Castrol GTX Diesel 15W-40 provides:

- Superior cleaning of engine sludge* caused by poor fuel quality, heat and frequent short trips
- Advanced protection against viscosity and thermal breakdown.
- Premium quality base oils and anti wear additives to help extend the life of your engine
- Helps minimize oil consumption.

* Vs API SP Limits

Typical Characteristics

Name	Method	Units	Castrol GTX Diesel 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.872
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	15.7
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	117
Viscosity Index	ASTM D2270	None	142
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	5874
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	202
Ash, Sulphated	ASTM D874	% wt	1.1

Product Performance Claims

ACEA A3/B4
API SP

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Diesel 15W-40
23 Nov 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz