



Product Data

Castrol Vecton Long Drain 10W-40 E8/E11

For longer useful oil life

Description

Castrol Vecton Long Drain 10W-40 E8/E11 is an advanced synthetic technology heavy duty diesel engine oil that is specifically engineered to deliver longer useful oil life.

Application

Castrol Vecton Long Drain 10W-40 E8/E11 is suitable for highly rated diesel engines meeting Euro I to Euro VI emission requirements. It is suitable for engines with or without particulate filters, and for most EGR engines and for most engines fitted with SCR NOx reduction systems. It is strongly recommended for engines fitted with particulate filters and is designed for use in combination with low sulphur diesel fuel.

Advantages

Modern trucks use new technologies to make as much as 30% higher torque, but this also means higher engine temperatures and pressures. This punishes the oil, pushing it closer to breakdown, and reducing its useful life and ability to extend drains. Castrol VECTON Long Drain's System Pro Technology™ has been proven to safely extend drain intervals up to 120,000kms*.

System Pro Technology fights oil breakdown by:

- combating oxidation and deposits
- neutralizing harmful acids
- controlling oil aeration
- adapting to increased temperatures
- resisting viscosity loss through shear.

All of this means longer useful oil life, giving you the confidence in your maximum drain interval.

*is approved by MAN for up to 120,000kms and Mercedes Benz, Volvo, and Renault for up to 100,000kms in accordance with their specifications. Actual oil drain depends on engine type, operating conditions, service history, OBD and fuel quality. Always consult your manufacturer's handbook.

Typical Characteristics

Name	Method	Units	Vector Long Drain 10W-40 E8/E11
Density @ 15C	ASTM D4052	g/ml	0.867
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	100
Viscosity Index	ASTM D2270	None	148
Pour Point	ASTM D97	°C	-36
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6610
Flash Point, PMCC	ASTM D93	°C	202
Total Base Number, TBN	ASTM D4739; ASTM D2896	mg KOH/g	8.3
Ash, Sulphated	ASTM D874	% w t	0.97

Performance

ACEA E6, E7, E8, E9, E11

API CK-4

JASO DH-2

CAT ECF-3

Cummins CES 20086

DDC DFS 93K222

Deutz DQC IV-18 LA

DTFR 15C100, DTFR 15C110, DTFR 15C120

Mack EOS-4.5

MAN M 3775

MTU Oil Category 3.1

RV1 RLD-3

Volvo CNG, VDS-4.5

Warranted by Castrol to be completely suitable for use where the following specifications apply: MAN M 3271-1, M 3271-3, M 3477

IVECO For trucks requiring ACEA E6, E7 and E9

DAF Meets Euro VI requirements

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Vector Long Drain 10W-40 E8/E11

19 Nov 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com