



Castrol Activ 4T 15W-50

with Actibond™

Description

Castrol Activ 4T with Actibond™ is modern, high quality engine oil developed specifically for 4-stroke motorcycle engines.

The special Actibond™ clings and protects critical engine components, providing continuous protection in all riding conditions.

Castrol Trizone Technology™ protects the engine, clutch and gears and allows the best functionality of these three critical areas of the motorcycle.

Application

Castrol Activ 4T is suitable for all 4-Stroke motorcycle engines where API SL (and below) and or JASO MA-2 and MA specifications are recommended.

Advantages

- Provides continuous protection even when the engine is off.
- Actibond™ molecules cling and protect during all riding conditions.
- Trizone Technology™ for protection of the engine, clutch and gears.
- Complies with requirements of catalyst equipped engines.

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	19.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	134
Viscosity Index	ASTM D2270	None	146
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.8

Product Performance Claims

API SL
JASO MA2

Removal

Bare Metal Surfaces: Remove with Castrol solvent cleaners or water based degreasers.
Hand Cleaning: Use any of the Castrol range of hand cleaners, e.g. Care Clean Plus.
Other Surfaces: Contact your local Technical Advice Line on 1300 557 998.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ 4T 15W-50
09 Jul 2014
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz