

Technical Data sheet

HARTEX 22-A

Water Scourable Textile Oil

Description

HARTEX 22-A is a superior quality, blended textile spindle and thread oil. It is completely scourable and does not stain or mark fabrics. It contains a premium anti-wear additive package designed to provide superior performance in the finished product. It forms a superior cling-ability with the high speed spindle mechanism and remains in position despite fluctuating speed actions. This quality ensures that all parts of the machinery are given absolute protection during high speed operations. HARTEX 22-A is also an excellent anti-static agent as it prevents the build-up of static electricity on the thread.

By using **HARTEX 22-A**, textile machinery can be operated at speeds of up to 20,000 rpm without the risk of thread breaking.

Typical Applications

HARTEX 22-A is designed for use with high speed knitting machines requiring an emulsifiable oil for lubrication of the needles and their beds.

Advantages

- Reduces Friction & Wear
- Incorporates Emulsifiers washes out readily in tap water
- Represses static buildup
- Low Odour improved operator comfort
- Non staining
- Protects machinery from wear & corrosion
- Environmentally beneficial product compared to mineral oil based products

Typical Properties

Name	Method	Results
Description	Visual	Transparent, pale straw coloured oily liquid
Density @ 15 °C	ASTM D1298	0.869
Flash Point, COC	ASTM D92	204°C
Kinematic Viscosity @ 40°C	ASTM D445	20.5 cSt
Oxidation resistance	ASTM D2272	Excellent
Emulsion Stability	1:10	No separation
Zinc %wt		0.04
Phosphorous %wt		0.03

Note: Data is typical and does not constitute a specification

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See www.ils.co.nz No responsibility is taken by either ILS LTD for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

INDUSTRIAL LUBRICANTS & SERVICES LTD PO BOX 259 347 GREENMOUNT MANUKAU 2163 AUCKLAND Tel: 0800 10 40 11