



## Technical Data sheet

# ILS Process Lubricants

## Additive Free Process Oils

### Description

ILS PL Lubricants are a range of additive free mineral process oils varying in composition from highly Napthenic to highly Paraffinic. These oils have been produced using solvent extraction of high vacuum distilled feedstock.

### Typical Applications

These process oils are suitable for use in a wide range of industrial applications ranging from rubber processing and extending through to metal quenching, printing inks, adhesives, polishes and paints, wood treatment & leather processing products.

### Typical Properties

Parameter	Test Method	Units	PL12	PL32	PL52	PL100	PL450
<b>Colour</b>	ASTM D1500	-	1.5	1.5	2.	<2.0	<4.5 max
<b>Appearance</b>		-	C & B	C & B	C & B	C & B	C & B
<b>Density @ 15 °C</b>	ASTM D1298	Kg/L	.885	.864	.867	.889	.915
<b>Kinematic Viscosity @ 40°C</b>	ASTM D445	cSt	10.15	30	52	113	480
<b>Kinematic Viscosity @ 100°C</b>	ASTM D445	cSt	2.6	5.3	7.6	11.7	29.9
<b>Viscosity Index</b>	ASTM D2270	-	81	111	110	91	95
<b>Flash Point, PMCC</b>	ASTM D92	°C	147	204	222	232	280
<b>Copper Strip</b>	ASTM D130	-	1A	1A	1A	1A	1A

<b>Corrosion (3 hrs @ 100°C)</b>							
<b>Pour Point</b>	ASTM D97	°C	-49	<-9	-9	-9	-3
<b>Total Acid Number</b>	ASTM D94	Mg(KOH ) /g	<0.01	0.01	0.01	0.02	0.03
<b>Sulphur</b>	IP 336	%w/w	-	0.50	0.50	0.78	1.1
<b>Hydrocarbon Type</b>							
<b>Paraffinic</b>	ASTM D2140	%w/w	44.0	66	68	62	68
<b>Aromatic</b>	ASTM D2140	%w/w	10.0	1	2	8	10
<b>Napthenic</b>	ASTM D2140	%w/w	46.0	33	30	30	22
<b>Water Content</b>	ASTM D6304	%vol	<20	.004	.004	.01 max	.01 max
<b>Aniline Point</b>	ASTM D611	°C	80	105	110	109	111

**Note: Data is typical and does not constitute a specification**

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See [www.ils.co.nz](http://www.ils.co.nz) No responsibility is taken by either ILS LTD for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.