

Technical Data sheet

ILS MEAT RAIL LUBE

A Vegetable Oil Based Dewatering Rail Lubricant

Description

ILS MEAT RAIL LUBE is a utilitarian rust inhibiting and dewatering vegetable oil based lubricant designed for use in meat processing plants for the lubrication of meat rails, chains, hooks and gimbols. The soft residual film is vegetable oil based and biodegradable and is easily removed with alkaline washing systems.

Typical Applications

ILS MEAT RAIL LUBE is designed for the lubrication of rails, chains, bars, pins and guides found in many meat processing applications.

Advantages

- Reduces Friction & Wear
- Ease of application through extended lube lines
- Excellent penetration of linkage & fastners
- Rust Preventative
- NZFSA Registered C22

Typical Properties

| Name | Method | Results |
|----------------------------|------------|---|
| Description | Visual | Transparent, amber coloured oily liquid |
| Density @ 15 °C | ASTM D1298 | 0.839 g/ml |
| Flash Point, PMCC | ASTM D93 | 37°C |
| Kinematic Viscosity @ 40°C | ASTM D445 | <7 cSt |
| HAZNO Category | 3.1C | Flammable Liquid |

Note: Data is typical and does not constitute a specification

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See www.ils.co.nz No responsibility is taken by either ILS LTD for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

INDUSTRIAL LUBRICANTS & SERVICES LTD PO BOX 259 347 GREENMOUNT MANUKAU 2163 AUCKLAND Tel: 0800 10 40 11