

Technical Data sheet

ILS BIOMOULD F

A Concrete Product Release Agent

Description

ILS BIOMOULD F is an environmentally friendly vegetable oil based biodegradable lubricant designed to facilitate the release of concrete products from molds during production.

Typical Applications

ILS BIOMOULD F is suitable for use in the manufacture of blocks, tiles, pipes, pavers and other concrete products using both steel and wooden molds.

It is designed to be used as a neat product.

Apply by pressure spray, brush or swab.

NOT SUITABLE FOR USE WITH POLYSTYRENE

Advantages

- · Suitable for pressed or extruded products
- Non staining
- Suitable for use with wood and steel moulds.
- Can be applied as a rust preventative on steel moulds after use.
- Leaves no residue which might interfere with downstream applications
- Low odour improved operator comfort
- Produced from a renewable resource
- Low toxicity
- Environmentally beneficial product compared to other oil based products

Typical Properties

Name	Method	Results
Description	Visual	Transparent, golden coloured oily liquid
Density @ 15 °C	ASTM D1298	0.874
Flash Point, PMCC (°C)	ASTM D93	>120°C

Note: Data is typical and does not constitute a specification

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See www.ils.co.nz No responsibility is taken by either ILS LTD for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

INDUSTRIAL LUBRICANTS & SERVICES LTD PO BOX 259 347 GREENMOUNT MANUKAU 2163 AUCKLAND Tel: 0800 10 40 11

Issue Date: 10/06/2020