

Technical Data sheet

ILS MAGNA AW 150

General Machine Lubricant

Description

ILS MAGNA AW 150 is formulated from premium quality refined base oils and contains anti-wear and a tackifying additive for application as a general lubricant to chains, slides, sprockets, and bearings as utilized in the sawmill industry.

Typical Applications

ILS MAGNA AW 150 is an excellent general machine lubricant which can be utilized in a central lubrication system as common in commercial Sawmill operations.

ILS MAGNA AW 100 is applicable for lubrication of chains, sprockets, slides, bearings and lightly loaded gearbox applications. Also suitable for lubrication of many debarker ring bearings.

Advantages

- Minimises throw off especially on large fast moving Sawmill Chain Systems.
- Minimises wear on chains, slides, bearings and may be applicable for lightly loaded gearboxes.
- May be dispensed from central lubrication system.

Typical Properties

| Name | Method | Units | AW 150 |
|--|---------------------------|-----------------------|----------------|
| Appearance | Visual | - | Clear & Bright |
| Density @ 15°C | ISO 12185 / ASTM D4052 | kg/m³ | 890 |
| Kinematic Viscosity @ 40°C | ISO 3104 / ASTM D445 | mm²/s | 150 |
| Kinematic Viscosity @ 100°C | ISO 3104 / ASTM D445 | mm²/s | 14.7 |
| Viscosity Index | ISO 2909 / ASTM D2270 | - | 96 |
| Pour Point | ISO 3016 / ASTM D97 | °C | -10 |
| Foam Sequence I - tendency / stability | ISO 6247 / ASTM D892 | ml/ml | 10/0 |
| Flash Point - closed cup method | ISO 2719 / ASTM D93 | °C | 220 |
| Rust test - synthetic seawater (24 hrs) | ISO 7120 / ASTM D665B | - | Pass |
| Copper corrosion (3 hrs@100°C/212°F) (24 hrs) | ISO 2160 / ASTM D130 | Rating | 1A |
| Four Ball Wear test - Wear Scar Diameter | IP 239 | mm | 0.3 |
| FZG Gear Scuffing test - A/8.3/90 | ISO 14635-1 | Failure Load Stage | >12 |

Note: Data is typical and does not constitute a specification

INDUSTRIAL LUBRICANTS & SERVICES LTD PO BOX 259 347 GREENMOUNT MANUKAU 2163 AUCKLAND Tel: 0800 10 40 11 This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See www.ils.co.nz No responsibility is taken by either ILS LTD for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

INDUSTRIAL LUBRICANTS & SERVICES LTD PO BOX 259 347 GREENMOUNT MANUKAU 2163 AUCKLAND Tel: 0800 10 40 11

Issue Date: 09/08/2019