

BIOSYNT 40V

FULLY SYNTHETIC MULTI-PURPOSE LUBRICANT / PENETRATING OIL / CORROSION INHIBITOR

Description

LUBECO™ BIOSYNT 40V is a premium, fully synthetic multi-purpose oil offering superior lubrication properties. It is characterized by excellent penetrating, preservative and moisture-displacing effects.

BIOSYNT 40V is readily biodegradable, non-toxic and user friendly. Specially developed to replace petroleum-based products.

Also available in aerosol application.

Areas of Application

BIOSYNT 40V is multi-use oil suitable for lubrication of all mechanical equipment and general use around industrial sites, workshops and homes e.g., machinery, tools, bicycles, guns, hinges, rusty locks, outdoor equipment, and countless other uses.

Characteristic features:

- Superior lubrication performance;
- Multi-purpose application;
- Excellent anti-rust and anti-corrosion protection;
- Non-toxic, user friendly;
- Readily biodegradable according to OECD 301B and OECD 301D

Typical characteristics

PARAMETER	UNIT	TEST METHOD	VALUE
Density at 15 °C	kg/m ³	ISO 12185	921
Kinematic Viscosity at 40°C (ISO VG)	mm ² /s	ISO 3104	48
Pour point	°C	ISO 3016	-35
Flash point, COC	°C	ISO 2592	> 300
Biodegradability (within 28 days)	%	OECD 301D	Exceeds

The above-listed data represent average values. Material Safety Data Sheet available on request.

Issue Date: 01.02.2022

