



## Aircol SN Range

Synthetic Air Compressor Lubricant

### Description

Castrol Aircol™ SN compressor lubricants are formulated using high quality synthetic diesters.

### Application

Castrol Aircol SN compressor lubricants are formulated to cope with the severe operating conditions experienced in rotary screw, rotary vane and reciprocating air compressors operating at high compression ratios and high discharge temperatures. Under these conditions Aircol SN compressor oils offer reduced carbon forming tendencies and extended oil life when compared to mineral oils due to their much higher oxidation resistance. In reciprocating units, Aircol SN grades have up to eight times the service life of mineral oils.

### Advantages

- Superior oxidation stability.
- Improved lubricity and film strength.
- Higher film strength and excellent anti-wear properties.
- Excellent high temperature performance.
- Reduced maintenance, extended oil life and cleaner operations, minimises carbon formulation and provides extended valve life.
- Reduced oil consumption due to a reduction in the required lubricant feed rate to the cylinder walls and piston rings without increasing wear rates. Since less lubricant is consumed the delivered compressed air is also of higher quality.
- Reduced compressor down-time due to less wear on all moving parts, longer machine life and reduced maintenance.
- The operating temperature range of Aircol SN grades extend beyond that of conventional mineral oils. The high spontaneous ignition temperature provides greater safety by reducing the possibility of downstream fires and explosions.

## Typical Characteristics

Name	Method	Units	Aircol SN 68	Aircol SN 100
ISO Viscosity Grade	-	-	68	100
Density @ 15°C	ISO 12185 / ASTM D4052	kg/m <sup>3</sup>	960	960
Kinematic Viscosity @ 40°C	ISO 3104 / ASTM D445	mm <sup>2</sup> /s	68	100
Kinematic Viscosity @ 100°C	ISO 3104 / ASTM D445	mm <sup>2</sup> /s	7.6	10.3
Viscosity Index	ISO 2909 / ASTM D2270	-	67	89
Flash Point - open cup method	ISO 2592 / ASTM D92	°C	>200	>200
Pour Point	ISO 3016 / ASTM D97	°C	-40	-40

Subject to usual manufacturing tolerances.

Aircol SN Range

05 Mar 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008

Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

<http://msdspd.castrol.com>